

## Hydraulic Adapters - NPTF

### 90° Male x Female Street Elbows

#### Specifications

- Reference 140239
- Pressure rating at 70°F (21°C)

| Male NPTF     | Female NPTF   | PSI  | Zinc Plated Steel Part # |
|---------------|---------------|------|--------------------------|
| 1/4"-18       | 1/4"-18       | 5000 | 5502-4                   |
| 3/8"-18       | 3/8"-18       | 4000 | 5502-6                   |
| 1/2"-14       | 1/2"-14       | 3000 | 5502-8                   |
| 3/4"-14       | 3/4"-14       | 2500 | 5502-12                  |
| 1"-11-1/2     | 1"-11-1/2     | 2000 | 5502-16                  |
| 1-1/4"-11-1/2 | 1-1/4"-11-1/2 | 1150 | 5502-20                  |



### 90° Male x Female NPSM Swivel Nut Elbows

#### Specifications

- Reference SAE 140230
- Pressure rating at 70°F (21°C)

| Male NPTF     | Female NPSM Swivel | PSI  | Zinc Plated Steel Part # |
|---------------|--------------------|------|--------------------------|
| 1/8"-27       | 1/8"-27            | 5000 | 1501-2-2                 |
| 1/4"-18       | 1/4"-18            | 4500 | 1501-4-4                 |
|               | 3/8"-18            | 4000 | 1501-4-6                 |
|               | 1/4"-18            | 4000 | 1501-6-4                 |
| 3/8"-18       | 3/8"-18            | 4000 | 1501-6-6                 |
|               | 1/2"-14            | 4000 | 1501-6-8                 |
|               | 3/8"-18            | 3000 | 1501-8-6                 |
| 1/2"-14       | 1/2"-14            | 3000 | 1501-8-8                 |
|               | 3/4"-14            | 3000 | 1501-8-12                |
|               | 1/2"-14            | 2500 | 1501-12-8                |
| 3/4"-14       | 3/4"-14            | 2500 | 1501-12-12               |
|               | 1"-11-1/2          | 2000 | 1501-12-16               |
|               | 3/4"-14            | 2000 | 1501-16-12               |
| 1"-11-1/2     | 1"-11-1/2          | 2000 | 1501-16-16               |
|               | 1-1/4"-11-1/2      | 1150 | 1501-16-20               |
| 1-1/4"-11-1/2 | 1-1/4"-11-1/2      | 1150 | 1501-20-20               |



K

### 90° Female Pipe Elbows

#### Specifications

- Reference SAE 140237
- Pressure rating at 70°F (21°C)

| Female NPTF | Female NPTF | PSI  | Zinc Plated Steel Part # |
|-------------|-------------|------|--------------------------|
| 1/8"-27     | 1/8"-27     | 5000 | 5504-2                   |
| 1/4"-18     | 1/4"-18     | 5000 | 5504-4                   |
| 3/8"-18     | 3/8"-18     | 4000 | 5504-6                   |
| 1/2"-14     | 1/2"-14     | 3000 | 5504-8                   |
| 3/4"-14     | 3/4"-14     | 2500 | 5504-12                  |
| 1"-11-1/2   | 1"-11-1/2   | 2000 | 5504-16                  |



### 90° Female x Female NPSM Swivel Nut Elbows

#### Specifications

- Reference SAE 140251
- Pressure rating at 70°F (21°C)

| Female NPTF | Female NPSM Swivel | PSI  | Zinc Plated Steel Part # |
|-------------|--------------------|------|--------------------------|
| 1/4"-18     | 1/4"-18            | 4500 | 1502-4-4                 |
| 3/8"-18     | 3/8"-18            | 4000 | 1502-6-6                 |
| 1/2"-14     | 1/2"-14            | 3000 | 1502-8-8                 |
| 3/4"-14     | 3/4"-14            | 2500 | 1502-12-12               |
| 1"-11-1/2   | 1"-11-1/2          | 2000 | 1502-16-16               |



### 45° Male x Female NPSM Swivel Nut Elbows

#### Specifications

- Reference SAE 140330
- Pressure rating at 70°F (21°C)

| Male NPTF | Female NPSM Swivel | PSI  | Zinc Plated Steel Part # |
|-----------|--------------------|------|--------------------------|
| 1/4"-18   | 1/4"-18            | 4500 | 1503-4-4                 |
| 3/8"-18   | 3/8"-18            | 4000 | 1503-6-6                 |
| 1/2"-14   | 1/2"-14            | 3000 | 1503-8-8                 |
| 3/4"-14   | 3/4"-14            | 2500 | 1503-12-12               |
| 1"-11-1/2 | 1"-11-1/2          | 2000 | 1503-16-16               |

