


Sight Glass End Caps - B5416MP

Feature

- For use on any line with a clamp and gasket

Specifications

- Maximum temperature: **150°F (66°C)**
- Maximum operating pressure: **100 PSI**



Tube O.D.	A (in)	B (in)	C (in)	D (in)	Acrylic Plastic Part #
1" - 1-1/2"	1.98	1.72	1.68	.50	B5416MP-A100150
2"	2.52	2.22	2.19	.50	B5416MP-A200
2-1/2"	3.05	2.78	2.71	.50	B5416MP-A250
3"	3.58	3.28	3.22	.50	B5416MP-A300
4"	4.68	4.34	4.26	.50	B5416MP-A400
6"	6.57	6.18	6.13	.50	B5416MP-A600
8"	8.57	8.17	8.22	.50	B5416MP-A600

Topping Gun - BTG

Features


- Squeeze handle for easy opening and control
- Spring loaded trigger for positive shutoff

Materials

- 304 stainless steel
- Seals and gaskets: EPDM

Specifications

- 1/2" female NPT inlet
- 3/4" O.D. tube outlet



A (in)	B (in)	C (in)	D (in)	Part #
8.094	3.38	4.75	4.56	BTG-G50

Repair Kits

Description	Part #
replacement Handle	BTG-HANDLE
repair kit - 1pc each - spring, piston, piston gasket (1/2" EPDM), plunger, plunger O-ring (nitrile rubber), cap O-ring (I.D. 17.0mm t 2.0mm nitrile rubber)	BTG-KIT

NOTE: Engineering dimensions are available upon request. Specifications are subject to change without notice.

Jax Food Grade Penetrating Oil

Features

- NSF H1 registered for incidental food contact
- Colorless, odorless, and tasteless
- Quickly frees corroded parts
- Protects metal from corrosion
- Lubricates moving parts



Description	Part #
16 fl.oz. trigger spray bottle	LUPO-16