

## Tri-Flo Fog Nozzles

### Features

- Corrosion resistant plated aluminum
- Combination 170° fog and straight stream
- Venturi flow improves straight stream and gallonage
- No nozzle teeth eliminates fingers and voids in the spray pattern thus producing a dense fog



| Size   | Thread | GPM @ 100 PSI<br>Straight Stream | 6061 T-6 Aluminum<br>Part # |
|--------|--------|----------------------------------|-----------------------------|
| 1-1/2" | NST    | 60-100-140                       | TFN150NST-140               |
|        | NPSH   |                                  | TFN150-140                  |
|        | NST    | 75-150-200                       | TFN150NST-200               |
|        | NPSH   |                                  | TFN150-200                  |

## Econo Fog Nozzles

### Application

- For cabinet use; discourages theft

### Features

- Rugged, lightweight, corrosion resistant
- Supplied without bumper

### Specification

- For use up to 100 PSI (water only)



| Size   | Thread | Straight Stream<br>@ 100 PSI | 6061-T6 Aluminum<br>Part # |
|--------|--------|------------------------------|----------------------------|
| 1"     | NPSH   | 56                           | AFN100                     |
|        | NST    |                              | AFN100NST                  |
| 1-1/2" | NPSH   |                              | AFN150                     |
|        | NST    |                              | AFN150NST                  |

## Heavy Duty Constant Flow Fog Nozzles

| Size   | Thread   | Length | GPM @<br>100 PSI | Fiberglass Reinforced Composite<br>Part # |
|--------|----------|--------|------------------|-------------------------------------------|
| 1-1/2" | NPSH     | 5"     | 95               | CFFR150                                   |
|        | NST (NH) |        |                  | CFFR150NST                                |

## Garden Hose Nozzles

### Features

- Offers two straight streams and one fog pattern<sup>1</sup>
- Massive bumper specially formulated to resist damage and aging
- Corrosion resistant hard coat



GHN75



GHN75-B

| Size | Thread               | GPM @ 40 PSI<br>Straight Stream |     | 6061-T6 Aluminum<br>Part # |
|------|----------------------|---------------------------------|-----|----------------------------|
|      |                      | 1st                             | 2nd |                            |
| 3/4" | GHT - without bumper | 1-2                             | 3-4 | GHN75                      |
|      | GHT - with bumper    |                                 |     | GHN75-B                    |

<sup>1</sup> Fog pattern is 4-5 GPM @ 40 PSI