

MSA - Storz x Rigid Male



1-1/2" x 1-1/2"

Storz Size	Male Thread	6061-T6 Forged Aluminum Part #
1-1/2"	1-1/2" NPT	MSA1515T
	1-1/2" NPSH	MSA1515S
	1-1/2" NST (NH)	MSA1515F
2"	1-1/2" NPT	MSA2015T
	1-1/2" NPSH	MSA2015S
	1-1/2" NST (NH)	MSA2015F
	2-1/2" CT*	MSA2025_*
2-1/2"	2" NPT	MSA2520T
	2-1/2" CT*	MSA2525_*
	2-1/2" NPT	MSA2525T
	2-1/2" NST (NH)	MSA2525F
	3" NPT	MSA2530T
3"	2-1/2" CT*	MSA3025_*
	2-1/2" NST (NH)	MSA3025F
	3" NPT	MSA3030T
4"	2-1/2" CT*	MSA4025_*
	2-1/2" NPT	MSA4025T
	2-1/2" NST (NH)	MSA4025F
	4" CT*	MSA4040_*
	4" NPT	MSA4040T
	4" NST (NH)	MSA4040F
	4-1/2" NST (NH)	MSA4045F
5"	2-1/2" CT*	MSA5025_*
	2-1/2" NST (NH)	MSA5025F
	4" CT*	MSA5040_*
	4" NPT	MSA5040T
6"	5" NST (NH)	MSA5050F
	6" NPT	MSA6060T



SLSA - Storz Live Swivel

Specification

- Working pressure: 200 PSI at 70°F (21°C)

Storz	FNPT	6061-T6 Forged Aluminum Part #
4"	4"	SLSA4040T
5"		SLSA5040T

NOTE: Optional configurations from 2-1/2" to 6" on the non-storz side.