

Thread Sealant Paste

Application

- Do not use with oxygen



Specification

- Temperature range: **-300°F to 500°F (-184°C to 260°C)**



Size	Part #	Optional Qty
1/4 pint	LCTS14	24
1/2 pint	LCTS1	24
1 pint	LCTS2	12
1 quart	LCTS3	12

Joint Sealant Gasket Material

Features

- GORE-TEX interchangeable
- Form-in-place expanded PTFE gasket material with adhesive backing
- Manufactured from 100% virgin PTFE
- Unaffected by all common chemicals (pH from 0-14)
- Unlimited shelf life
- Resilient with low cold flow
- Requires less force than standard gasket materials
- Made in the USA
- Larger spools are available; consult Dixon® for price and availability

Specifications

- Pressure range: **vacuum to 3000 PSI**
- Temperature range: **-450°F to 600°F (-268°C to 316°C)**



Approval

- FDA compliant #21CFR177.1550

Size	Length	Part #
1/4"	20'	LCJS4-20
1/4"	50'	LCJS4-50
3/8"	25'	LCJS6-25
1/2"	15'	LCJS8-15
3/4"	15'	LCJS12-15

Leak Detector

Application

- Detects leaks by forming bubbles which remain for up to ten minutes

Features

- Will not cause corrosion or deterioration
- Color: fluorescent yellow
- Non-toxic, non-freezing

Specification

- Temperature range: **-7°F to 180°F (-20°C to 82°C)**

Approval

- Meets Federal specification MIL-L-25567-C



Size	Part #	Case Qty
8 oz.	LCLD	24

