



The Right Connection®

Dixon Suction Hose

SPECIFICATION SHEET

PVC Flexible Suction Hose

- Ultra flexible and lightweight, one-man hook-up operation if necessary
- Designed for full vacuum
- Couplings – NO PLASTIC PARTS
- Maximum operating pressure range from 47 - 68 PSI dependent on the hose size
- Sizes - 2½", 3", 4", 4½", 5" and 6" standard. Other diameters available upon request
- Lengths - 10' standard length
- Couplings - Provincial threads, Storz and NST ends

Size	Length	Thread	Female L/H x Male Part #	Female R/L x Male Part #	Storz x Storz Part #
2½"	10'	NST	FSH-9682-000	FSH-9682-050F	
		BAT	FSH-9682-000B		
		CSA	FSH-9682-000C	FSH-9682-050C	
		WCT	FSH-9682-000W	FSH-9682-050W	
3"	10'	NH	FSH-9682-100	FSH-9682-150	
4"		NH	FSH-9682-200	FSH-9682-250	FSH-9682-220
4½"		NH	FSH-9682-300		
5"		NH	FSH-9682-400	FSH-9682-450	FSH-9682-420
6"		NH	FSH-9682-500	FSH-9682-550	FSH-9682-520

Note: different lengths and configurations are available, contact Dixon for details. Pictures shown may vary from actual products.

Dixon Group Canada Limited

2200 Logan Avenue
 Winnipeg, MB R2R 0J2
 ph: 877.963.4966
 email: isales@dixonvalve.ca
canada.dixonvalve.com