

Polyurethane Whip Hose

fittings included



Features:

- bright orange
- for use with jack hammers, chipping hammers, rock drills and other large pneumatic tools
- ½" male NPT swivels on each end
- abrasion resistant
- oil and grease resistant
- working pressure: **200 PSI at 70°F (21°C)**
- strain relief steel spring bend restrictors

Hose ID	Length	Male NPT	Part #
½"	6'	½"	PFD068
½"	10'	½"	PFD108
½"	25'	½"	PFD125

Polyurethane Air Hose

fittings included

Application:

- A sturdy, nylon-reinforced braid between the inner and outer tube allows for a higher working pressure.



Features:

- durable
- lightweight
- excellent flexibility
- oil resistant
- durometer: Shore A 85
- temperature range: **-40°F to 155°F (-40°C to 68°C)**
- working pressure: **210 PSI at 70°F (21°C)**

Hose ID	Length	Male NPT	Part #
1/4"	50'	1/4"	450-4S
3/8"	50'	1/4"	650-4S
3/8"	50'	3/8"	650-6S

Polyurethane Self-Storing Air Hose

fittings included

Features:

- extremely flexible - resists kinking
- impervious to abrasions, heat and oil
- superior elasticity and coil memory
- blue
- polyurethane working pressure: **125 PSI at 70°F (21°C)**
- both ends swivel



Hose ID	Length	Male NPT	Part #
1/4"	10'	1/4"	PU1410
1/4"	15'	1/4"	PU1415
1/4"	25'	1/4"	PU1425
3/8"	15'	3/8"	PU3815
3/8"	20'	3/8"	PU3820
3/8"	25'	3/8"	PU3825
3/8"	50'	3/8"	PU3850
1/2"	15'	1/2"	PU1215

Repair Kits



Tubing Size		Size	Type	Part #
ID	OD			
1/4"	3/8"	1/4"	swivel male	PSM0404
3/8"	9/16"	1/4"	swivel male	PSM0604