

## Dix-Lock Quick Acting Couplings

### Features:

- Dix-Lock is rated to **300 PSI** at ambient temperature (21°C, 70°F)

### Male Head x Female NPT End

| Body Size | NPT Thread Size | Material      | Old Part # | Part #        | Opt Qty |
|-----------|-----------------|---------------|------------|---------------|---------|
| 1/2"      | 3/8"            | plated steel  | QM81       | <b>N4F3</b>   | 25      |
| 1/2"      | 1/2"            | plated steel  | QM82       | <b>N4F4</b>   | 25      |
| 1/2"      | 3/4"            | plated steel  | QM83       | <b>N4F6</b>   | 25      |
| 1/2"      | 1"              | plated steel  | QM85       | <b>N4F8</b>   | 25      |
| 1/2"      | 3/8"            | brass         | QB81       | <b>N4F3-B</b> | --      |
| 1/2"      | 1/2"            | brass         | QB82       | <b>N4F4-B</b> | --      |
| 1/2"      | 3/4"            | brass         | QB83       | <b>N4F6-B</b> | --      |
| 1/2"      | 1"              | brass         | QB85       | <b>N4F8-B</b> | 25      |
| 1/2"      | 3/4"            | 303 stainless | QSS83      | <b>N4F6-S</b> | --      |



E

### Female Head x Female NPT End

| Body Size | NPT Thread Size | Material      | Old Part # | Part #        | Opt Qty |
|-----------|-----------------|---------------|------------|---------------|---------|
| 1/2"      | 3/8"            | plated steel  | QM101      | <b>4NF3</b>   | 25      |
| 1/2"      | 1/2"            | plated steel  | QM102      | <b>4NF4</b>   | 25      |
| 1/2"      | 3/4"            | plated steel  | QM103      | <b>4NF6</b>   | 25      |
| 1/2"      | 1"              | plated steel  | QM105      | <b>4NF8</b>   | 25      |
| 1/2"      | 3/8"            | brass         | QB101      | <b>4NF3-B</b> | --      |
| 1/2"      | 1/2"            | brass         | QB102      | <b>4NF4-B</b> | --      |
| 1/2"      | 3/4"            | brass         | QB103      | <b>4NF6-B</b> | --      |
| 1/2"      | 1"              | brass         | QB105      | <b>4NF8-B</b> | 25      |
| 1/2"      | 3/4"            | 303 stainless | QSS103     | <b>4NF6-S</b> | --      |



### Male Locking Head x Hose Shank

| Body Size | Hose Shank Size | Material      | Old Part # | Part #           |
|-----------|-----------------|---------------|------------|------------------|
| 1/2"      | 1/2"            | plated steel  | QM33       | <b>N4S4-LS</b>   |
| 1/2"      | 3/4"            | plated steel  | QM44       | <b>N4S6-LS</b>   |
| 1/2"      | 1/2"            | brass         | QB33       | <b>N4S4-B-LS</b> |
| 1/2"      | 3/4"            | brass         | QB44       | <b>N4S6-B-LS</b> |
| 1/2"      | 1"              | 303 stainless | QSS44      | <b>N4S6-S-LS</b> |



### Male Locking Head x Male NPT

| Body Size | NPT Thread Size | Material      | Old Part # | Part #           |
|-----------|-----------------|---------------|------------|------------------|
| 1/2"      | 1/2"            | plated steel  | QM66       | <b>N4M4-LS</b>   |
| 1/2"      | 3/4"            | plated steel  | QM88       | <b>N4M6-LS</b>   |
| 1/2"      | 1/2"            | brass         | QB66       | <b>N4M4-B-LS</b> |
| 1/2"      | 3/4"            | brass         | QB88       | <b>N4M6-B-LS</b> |
| 1/2"      | 1"              | 303 stainless | QSS88      | <b>N4M6-S-LS</b> |



*Positive safety lock*

With locking nut in place sleeve cannot be moved to open coupling.

## Dix-Lock Gaskets

| Body Size | Material | Old Part # | Part #           |
|-----------|----------|------------|------------------|
| 3/8"      | Buna-N   | QBM1       | <b>3N-SKIT</b>   |
| 1/2"      | Buna-N   | QBM2       | <b>4N-SKIT</b>   |
| 1/2"      | Viton    | ---        | <b>F-4N-SKIT</b> |

