


Series 1 Oil-Fog Lubricators

Application:

- Oil-fog lubricators, identified by a green adjusting screw, are used for lubricating a single air tool or air motor, and are located as near the device as possible.
- All the oil visible dropping through the transparent sight-feed dome goes to the airstream.
- L72C, L73C and L74C OIL-FOG lubricators can be filled under pressure.



** minimum clearance required to remove bowl

Features:

- 2 oz. reservoir
- in-line or modular installation
- quick release bayonet bowl
- micro-fog design delivers aerosol mist
- can be filled under pressure
- recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at 100°F (38°C)
- maximum operating conditions:
transparent bowl: **150 PSI** and **125°F (52°C)**
metal bowl: **250 PSI** and **175°F (79°C)**

Sub-Compact

Port Size	SCFM	Transparent Bowl Part #	Metal Bowl Part #
1/4"	51	L72C-2	L72C-2MB
3/8"	51	L72C-3	L72C-3MB




with transparent bowl

Features:

- 4 oz. reservoir
- in-line or modular installation
- quick release bayonet bowl
- micro-fog design delivers aerosol mist
- can be filled under pressure
- recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at 100°F (38°C)
- maximum operating conditions:
transparent bowl: **150 PSI** and **125°F (52°C)**
metal bowl: **250 PSI** and **175°F (79°C)**

Compact

Port Size	SCFM	Transparent Bowl Part #	Metal Bowl Part #
1/4"	60	L73C-2	L73C-2MB
3/8"	60	L73C-3	L73C-3MB
1/2"	60	L73C-4	L73C-4MB



with metal bowl

See pages 268-269 for lubricator accessories. See page 160 for air tool lubricant.



FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 90 PSIG inlet pressure.