

External Swage Notched NOS Stems and Ferrules

⚠ WARNING

- The notched system allows you to better manage your inventories. You can stock one stem and two ferrules, and cover the same hose range with less inventory. *You must purchase a fitting and the matching ferrule to create an assembly.*

Features:

- For hose outside diameters of 2-4/64" and below, *the couplings are crimp only.*
- For hose outside diameters of 2-5/64" and above, the couplings can be crimped or swaged.
- See page 53 for cam and groove style notched NOS fittings.



STC200NOS



RST200NOS



Only use the NOS shank with the NOS ferrules.

Due to differences in dimensions and tolerances for safety reasons, do not use other manufacturer's stems or ferrules with Dixon Holedall products.

stems

Size	PSI	Plated Carbon Steel Part #	316 Stainless Steel Part #
1½"	250	STC150NOS	RST150NOS
2"	250	STC200NOS	RST200NOS
3"	250	STC300NOS	RST300NOS
4"	*	STC400NOS	RST400NOS

* Contact Dixon for pressure information

ferrules



Size	Hose OD		Carbon Steel Part #	304 Stainless Steel Part #
	From:	To:		
1½"	1-60/64"	2-12/64"	CAS2334NOS	GAS2334NOS
1½"	2-4/64"	2-22/64"	CAS2370NOS	GAS2370NOS
2"	2-30/64"	2-44/64"	CAS2709NOS	GAS2709NOS
2"	2-42/64"	2-54/64"	CAS2885NOS	GAS2885NOS
3"	3-30/64"	3-46/64"	CAS3760NOS	GAS3760NOS
3"	3-47/64"	3-54/64"	CAS3885NOS	GAS3885NOS
4"	4-40/64"	4-47/64"	CAS5010NOS	GAS5010NOS

Jump Size King Combination Nipples

hose shank x NPT threaded end



reducer



increaser

Hose Shank	Male NPT	Plated Steel Part #	304 Stainless Steel Part #
¾"	½"	---	RST0501
¾"	1"	STC0510	RST0510
1"	¾"	STC1005	RST1005
1"	1¼"	STC1015	RST1015
1¼"	1"	STC1510	RST1510
1¼"	1½"	STC1520	RST1520
1½"	1¼"	STC2015	RST2015
1½"	2"	STC2025	RST2025
1¾"	2"	STC175200	---
2"	1½"	STC2520	RST2520
2"	2½"	STC2530	---
2"	3"	STC2535	RST2535
2½"	2"	STC3025	---
2½"	3"	STC3035	---
3"	2"	STC3525	RST3525
3"	2½"	STC3530	---
3"	4"	STC3540	---
4"	3"	STC4035	---