



## Series 1 Filter / Regulators

### Features:


- 5-150 PSI range
- in-line or modular installation
- 40 micron element
- 2 oz. reservoir
- quick-release bayonet bowl
- prismatic lens liquid level indicator
- particle removal per ISO 8573-1, Class 5 and Class 3
- supplied with GC620 gauge
- inlet pressure: transparent bowl: **150 PSI** at ambient temperature 70°F (21°C)  
metal bowl: **250 PSI** at ambient temperature 70°F (21°C)




1/4 Turn Manual Drain  
\*\* minimum clearance required to remove bowl




Semi auto Drain  
\*\* minimum clearance required to remove bowl




1/4 Turn Manual Drain  
\*\* minimum clearance required to remove bowl



Automatic Drain  
\*\* minimum clearance required to remove bowl



Manual Drain  
\*\* minimum clearance required to remove bowl



Automatic Drain  
\*\* minimum clearance required to remove bowl

### Sub-Compact with Transparent Bowl

Port Size	SCFM	Semi-Automatic Drain Part #	Manual Drain Part #
1/4"	80	<b>B72G-2AG</b>	<b>B72G-2MG</b>
3/8"	80	<b>B72G-3AG</b>	<b>B72G-3MG</b>

### Sub-Compact with Metal Bowl and Sight Glass

Port Size	SCFM	Semi-Automatic Drain Part #	Manual Drain Part #
1/4"	80	<b>B72G-2AG-MB</b>	<b>B72G-2MG-MB</b>
3/8"	80	<b>B72G-3AG-MB</b>	<b>B72G-3MG-MB</b>

### Features:

- 5-150 PSI range
- in-line or modular installation
- 40 micron element
- 3.5 oz. reservoir
- quick-release bayonet bowl
- prismatic lens liquid level indicator
- particle removal per ISO 8573-1, Class 5 and Class 3
- supplied with GC230 gauge
- inlet pressure: transparent bowl: **150 PSI** at ambient temperature 70°F (21°C)  
metal bowl: **250 PSI** at ambient temperature 70°F (21°C)

### Compact with Transparent Bowl

Port Size	SCFM	Automatic Drain Part #	Manual Drain Part #
1/4"	78	<b>B73G-2AG</b>	<b>B73G-2MG</b>
3/8"	123	<b>B73G-3AG</b>	<b>B73G-3MG</b>
1/2"	123	<b>B73G-4AG</b>	<b>B73G-4MG</b>

### Compact with Metal Bowl and Sight Glass

Port Size	SCFM	Automatic Drain Part #	Manual Drain Part #
1/4"	78	<b>B73G-2AG-MB</b>	<b>B73G-2MG-MB</b>
3/8"	123	<b>B73G-3AG-MB</b>	<b>B73G-3MG-MB</b>
1/2"	123	<b>B73G-4AG-MB</b>	<b>B73G-4MG-MB</b>

### Features:

- 5-125 PSI range
- 40 micron element
- 7 oz. reservoir
- relieving type
- supplied with GC230 gauge
- inlet pressure: transparent bowl: **150 PSI** at ambient temperature 70°F (21°C)  
metal bowl: **250 PSI** at ambient temperature 70°F (21°C)

### Standard with Transparent Bowl and Guard

Port Size	SCFM	Automatic Drain Part #	Manual Drain Part #
3/8"	163	<b>B74G-3AG</b>	<b>B74G-3MG</b>
1/2"	212	<b>B74G-4AG</b>	<b>B74G-4MG</b>
3/4"	212	<b>B74G-6AG</b>	<b>B74G-6MG</b>

### Standard with Metal Bowl and Sight Glass

Port Size	SCFM	Automatic Drain Part #	Manual Drain Part #
3/8"	163	<b>B74G-3AG-MB</b>	<b>B74G-3MG-MB</b>
1/2"	212	<b>B74G-4AG-MB</b>	<b>B74G-4MG-MB</b>
3/4"	212	<b>B74G-6AG-MB</b>	<b>B74G-6MG-MB</b>

See page 270 for filter/regulator accessories.



FRL's are designed for air service only, unless otherwise indicated.



with transparent bowl



with metal bowl



with transparent bowl



with metal bowl



with guard



with metal bowl

E

SCFM ratings at 150 PSIG inlet pressure.