

Wilkerson Miniature Combination Units (Filter, Regulator, Lubricator)

Features:

- maximum operating conditions:
transparent bowl: **150 PSIG** (10.3 bar) and **32°F to 125°F** (0°C to 52°C)
metal bowl: **250 PSIG** (17.2 bar) and **32°F to 175°F** (0°C to 80°C)

Filter series F03:


- 5 micron element
- .5 oz. bowl

Regulator series R03:

- 2-125 PSI adjusting range
- balanced valve design
- self-relieving
- supplied with a GC620 gauge
- Regulator can be mounted with knob in up or down position.

Lubricator series L03:

- 1 oz. bowl
 - adjustable oil feed
 - full view sight dome
- Included components:
- (2) adapters



1.60 (41)
Bowl Removal
Clearance



transparent bowl

Size	SCFM	With Transparent Bowl and Guard		With Metal Bowl	
		Automatic Drain Part #	Manual Drain Part #	Automatic Drain Part #	Manual Drain Part #
1/8"	20	C03-01A	C03-01M	C03-01AMB	C03-01MMB
1/4"	20	C03-02A	C03-02M	C03-02AMB	C03-02MMB

Features:

- maximum operating conditions:
transparent bowl: **150 PSIG** (10.3 bar) and **32°F to 125°F** (0°C to 52°C)
metal bowl: **250 PSIG** (17.2 bar) and **32°F to 150°F** (0°C to 65.5°C)

Filter series F08:


- 5 micron element
- .4 oz. bowl

Regulator series R08:

- 0-125 PSI adjusting range
- balanced valve design
- self-relieving
- supplied with a 0-160 PSI flush mount style gauge

Lubricator series L08:

- .6 oz. bowl
 - adjustable oil feed
 - full view sight dome
- Included components:
- (2) mounting brackets with joiner set



1.31 (33)
Bowl Removal
Clearance



metal bowl

Size	SCFM	With Transparent Bowl and Guard		With Metal Bowl	
		Automatic Drain Part #	Manual Drain Part #	Automatic Drain Part #	Manual Drain Part #
1/8"	29	C08-01A	C08-01M	C08-01AMB	C08-01MMB
1/4"	44	C08-02A	C08-02M	C08-02AMB	C08-02MMB



FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 150 PSIG inlet pressure.