


Wilkerson Miniature Filters



transparent bowl



Features:


- excellent water removal efficiency
- 5 micron element
- .5 oz. bowl
- maximum operating conditions:
transparent bowl: **150 PSIG** (10 bar) and **32°F to 125°F** (0°C to 52°C)
metal bowl: **250 PSIG** (17 bar) and **32°F to 175°F** (0°C to 80°C)

E

Size	SCFM	With Transparent Bowl		With Metal Bowl	
		Automatic Drain Part #	Manual Drain Part #	Automatic Drain Part #	Manual Drain Part #
1/8"	22	F03-01A	F03-01M	F03-01AMB	F03-01MMB
1/4"	24	F03-02A	F03-02M	F03-02AMB	F03-02MMB



metal bowl




Features:

- 5 micron element
- .4 oz. bowl
- maximum operating conditions:
transparent bowl: **150 PSIG** (10 bar) and **32°F to 125°F** (0°C to 52°C)
metal bowl: **250 PSIG** (17 bar) and **32°F to 150°F** (0°C to 65.5°C)

Size	SCFM	With Transparent Bowl and Guard		With Metal Bowl	
		Automatic Drain Part #	Manual Drain Part #	Automatic Drain Part #	Manual Drain Part #
1/8"	25	F08-01A	F08-01M	F08-01AMB	F08-01MMB
1/4"	50	F08-02A	F08-02M	F08-02AMB	F08-02MMB

See pages 212-215 for filter accessories.

Wilkerson Miniature Regulators



Features:

- 2-125 PSI adjusting range
- balanced valve design
- self-relieving standard
- non-rising push/pull locking adjustment knob
- two 1/8" NPT gauge ports standard on models without gauge, one 1/8" NPT gauge port standard on models with gauge - can be used for additional outlet ports.
- models supplied without gauge use a GC620 gauge.
- panel mount nuts sold separately
- maximum operating conditions:
300 PSIG (20.17 bar) and **32°F to 125°F** (0°C to 52°C)

Size	SCFM	With Gauge Part #	Without Gauge Part #
1/8"	13	R03-01RG	R03-01R
1/4"	15	R03-02RG	R03-02R

See pages 239-241 for regulator accessories.



FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 150 PSIG inlet pressure.