

Dixon Northline Wye Connectors

Application:

This lightweight, compact wye connection is used to supply two smaller lines from a large diameter hose.

Features:

- can be used to distribute water in the opposite direction
- does not come with clappers
- Storz connection inlet and (2) 2½" male outlets
- up to **280 PSI** working pressure at 70°F (21°C)
- water way: 1 inlet - 4½" maximum, 2 outlet side - 2½" maximum
- material: *high strength aluminum alloy, 356-T6*
- finish hardcoat anodized throughout - minimum thickness 0.001"



2-Way Wye Connectors

Inlet Storz	(2) Outlet	Alum. alloy, 356-T6 Part #	Length	Width	Height	Wt. Lbs.
4"	2½" Male	MSSV425 ¹	9.25"	8.00"	6.0"	7.0
5"	2½" Male	MSSV525 ¹	9.50"	8.00"	7.5"	8.5
6"	2½" Male	MSSV625 ¹	9.50"	8.00"	8.0"	8.5

¹ Customer Thread (*must specify*) refer to legend on page 705



3-Way Wye Connectors

Inlet Storz	(3) Outlet	Alum. alloy, 356-T6 Part #	Length	Width	Height	Wt. Lbs.
4"	2½" Male	MSSV3-425 ¹	11.75"	13.25"	7.5"	13.5
5"	2½" Male	MSSV3-525 ¹	11.75"	13.25"	8.0"	14.5
6"	2½" Male	MSSV3-625 ¹	11.75"	13.25"	8.0"	15.0

¹ Customer Thread (*must specify*) refer to legend on page 705



4-Way Wye Connectors

Inlet Storz	(4) Outlet	Alum. alloy, 356-T6 Part #	Length	Width	Height	Wt. Lbs.
4"	2½" Male	MSSV4-425 ¹	12.75"	16.75"	7.5"	17.0
5"	2½" Male	MSSV4-525 ¹	12.75"	16.75"	8.0"	17.5
6"	2½" Male	MSSV4-625 ¹	12.75"	16.75"	8.0"	17.5

¹ Customer Thread (*must specify*) refer to legend on page 705

Dixon Northline Jumbo Wye / Siamese

Application:

This jumbo "collector" is used to supply one large diameter hose from two large diameter hose lines. The jumbo Siamese is hard coat anodized throughout. Sometimes referred to as a jumbo wye, this Siamese is available with Storz fittings or threaded combinations. It can be used to distribute water in the opposite direction.

Features:

- up to **280 PSI** working pressure without relief valve at 70°F (21°C)
- water way: 2 inlet side - 4" maximum, 1 outlet - 4½" maximum.
- material: *high strength aluminum alloy, 356-T6*
- finish hardcoat anodized throughout - minimum thickness 0.001"



Inlet Storz	(2) Inlet Storz	Alum. alloy, 356-T6 Part #	Length	Width	Height	Wt. Lbs.
4"	4"	SSVJ440	12.50"	13.25"	6.5"	15.0
5"	4"	SSVJ540	12.75"	13.25"	8.0"	16.0
5"	5"	SSVJ550	13.75"	13.25"	8.0"	19.0