

Features:

- supplied with bumper
- delivers 30° - 60° - 90° fog pattern - shut-off - straight stream - fog
- for use up to **175 PSI** (water only) at 70°F (21°C)
- U/L listed and Factory Mutual approved for class A and B fires (except noted *)

Industrial Fog Nozzles

Size	Thread	90° Spray GPM @ 100PSI	Brass Part #	Wt. Lbs.
¾"	GHT	---	BFN75GHT *	1.3
¾"	NPSH	---	BFN75	1.4
1"	NPSH	36	BFN100	1.2
1½"	NPSH	85	BFN150	1.5
2"	NPSH	108	BFN200 *	2.9
1"	NH (NST)	36	BFN100NST	1.2
1½"	NH (NST)	85	BFN150NST	1.5
2½"	NH (NST)	205	BFN250NST *	3.3
2½"	CT ¹	205	BFN250	3.3



¹ Customer Thread (*must specify*) refer to legend on page 705

Heavy Duty Industrial Fog Nozzles**Features:**

- supplied with bumper
- delivers 30° - 60° - 90° fog pattern - shut-off - straight stream - fog
- for use up to **175 PSI** (water only) at 70°F (21°C)
- U/L listed and Factory Mutual approved

Size	Thread	90° Spray GPM @ 100PSI	Brass Part #	Wt. Lbs.
1"	NPSH	---	HFN100	2.2
1½"	NPSH	88 (+/-12)	HFN150	2.4
1"	NH (NST)	---	HFN100NST	2.2
1½"	NH (NST)	88 (+/-12)	HFN150NST	2.4
1½"	NYFD	---	HFN150NYFD	2.4

**Higher Pressure Industrial Fog Nozzles****Features:**

- large one-piece rubber bumper with molded teeth
- combination straight stream and fog - shut-off - straight stream - fog
- knurled base
- for use from **25 to 300 PSI** (water only) at 70°F (21°C)
- Factory Mutual approved

Size	Thread	90° Spray GPM @ 100PSI	Brass Part #	Wt. Lbs.
1½"	NPSH	117	HPFN150	1.9
1½"	NH (NST)	117	HPFN150NST	2.0

**Industrial Washdown Nozzles****Features:**

- shut off - straight stream - fog
- delivers 30° - 60° - 90° fog pattern
- supplied with bumper
- for use up to **100 PSI** (water only) at 70°F (21°C)

Size	Thread	90° Spray GPM @ 100PSI	Brass Part #	Wt. Lbs.
1½"	NPSH	88 (+/-12)	WDN150	1.5
1½"	NST (NH)	88 (+/-12)	WDN150NST	1.5

