

400# Nitrile Covered Fire Hose - Light Duty Red

Application:

- Ideal for industrial and construction washdown and discharge applications.

Features:

- outer construction: *thin ribbed nitrile*
- tube construction: *nitrile*
- ratings:
 - proof pressure: **400 PSI** at 70°F (21°C)
 - service test pressure: **200 PSI** at 70°F (21°C)
 - working pressure: **180 PSI** at 70°F (21°C)



Uncoupled

Size	Bowl	Length	Part #
2"	2-1/4"	50'	H420R50UC

Coupled

NPSH Thread

Size	Coupling Type	Length	Part #
2"	rocker lug, brass	50'	H420R50RBS

Consult Dixon for pricing and availability for any of the following features:

- other lengths, threads and couplings

500# Nitrile Covered Fire Hose - Light Duty Red

Application:

- Ideal for industrial and construction washdown and discharge applications.

Features:

- outer construction: *thin, ribbed nitrile*
- tube construction: *nitrile*
- ratings:
 - proof pressure: **500 PSI** at 70°F (21°C)
 - service test pressure: **250 PSI** at 70°F (21°C)
 - working pressure: **225 PSI** at 70°F (21°C)

Uncoupled

Size	Bowl	Length	Part #
1½"	1-13/16"	50'	H515R50UC
1½"	1-13/16"	100'	H515R100UC
2½"	2-13/16"	50'	H525R50UC

Coupled

NH (NST) Thread

Size	Coupling Type	Length	Part #
1½"	rocker lug, aluminum	50'	H515R50RAF
1½"	rocker lug, aluminum	100'	H515R100RAF
1½"	rocker lug, brass	50'	H515R50RBF
1½"	rocker lug, brass	100'	H515R100RBF
2½"	rocker lug, aluminum	50'	H525R50RAF
2½"	rocker lug, aluminum	100'	H525R100RAF
2½"	rocker lug, brass	50'	H525R50RBF

NPSH Thread

Size	Coupling Type	Length	Part #
1½"	rocker lug, aluminum	50'	H515R50RAS
1½"	rocker lug, aluminum	100'	H515R100RAS
2½"	rocker lug, aluminum	50'	H525R50RAS

Consult Dixon for pricing and availability for any of the following features:

- other lengths, threads and couplings
- other colors: yellow, red, blue and black