

Flat Seal Coupling Assemblies

Application:

- Designed for use on lay flat hose and single jacket fire hose with a wall thickness between 5/64" and 3/16".

Features:

- Flat seal couplings are for use with flat seal clamps only.
- brass swivel nut on complete assembly and female assemblies
- maximum recommended torque 40 ft/lbs
- Torque values for clamps are based on dry bolts. The use of lubricants on bolts will adversely effect clamp performance.



Complete Flat Seal Assembly - NPSM

Size	Aluminum Part #
1½"	FS150
2½"	FS250

Female Flat Seal Assembly - NPSM

Size	Aluminum Part #
1½"	FSF150
2½"	FSF250

Male Flat Seal Assembly - NPSM

Size	Aluminum Part #
1½"	FSM150
2½"	FSM250

Complete Flat Seal Assembly - NST (NH)

Size	Aluminum Part #
1½"	FS150F
2½"	FS250F

Female Flat Seal Assembly - NST (NH)

Size	Aluminum Part #
1½"	FSF150F
2½"	FSF250F

Male Flat Seal Assembly - NST (NH)

Size	Aluminum Part #
1½"	FSM150F
2½"	FSM250F

Male Flat Seal Assembly - NPT

Size	Aluminum Part #
1½"	FSM150T
2"	FSM200T
2½"	FSM250T

¹ price includes clamps



complete assembly



female Flat Seal
NPSM



male Flat Seal
NPSM



male Flat Seal
NPT

Flat Seal Gaskets

Size	Buna Part #
1½"	FSG150
2"	FSG200
2½"	FSG250
3"	FSG300
4"	FSG400

