


500# All Polyester Rack Hose - Brass Couplings non-UL Labeled

Features:

- outer construction: *single jacket, all polyester*
- tube construction; *clear thermoplastic*
- ratings:
 proof pressure: **500 PSI** at 70°F (21°C)
 service test pressure: **250 PSI** at 70°F (21°C)
 working pressure: **225 PSI** at 70°F (21°C)

- **Not** to be used for washdown
For pin rack service / emergency fire fighting only. 

Coupled with female and male brass expansion ring couplings

Size	Length	Thread	Folded Part #	Coiled Part #
1½"	50'	NST	R515-50CBF/F	R515-50CBF
1½"	100'	NST	R515100CBF/F	R515100CBF



folded




coiled

500# All Polyester Rack Hose - Brass Couplings UL Labeled

Features:

- outer construction: *single jacket, all polyester*
- tube construction; *clear thermoplastic*
- ratings:
 proof pressure: **300 PSI** at 70°F (21°C)
 service test pressure: **150 PSI** at 70°F (21°C)
 working pressure: **135 PSI** at 70°F (21°C)
- Underwriters Listed

- **Not** to be used for washdown
For pin rack service / emergency fire fighting only. 

Coupled with female and male brass expansion ring couplings

Size	Length	Thread	Folded Part #	Coiled Part #
1½"	50'	NST	R515U50CBF/F	R515U50CBF
1½"	100'	NST	R515U100CBF/F	R515U100CBF



folded



coiled