

## Dixon Northline Adapters

### N54 - Angle and Suction Elbows

**Features:**

- ideal for fire apparatus with front suction connections
- constructed with anodized, powder coated elbow, extruded
- anodized female swivel connections



90° elbow

Elbow Degree	Male NH (NST)	Female Swivel	Aluminum Part #	Wt. Lbs
30°	2½"	2½"	<b>N5430-250F</b>	2.0
45°	2½"	2½"	<b>N5445-250F</b>	2.0
60°	2½"	2½"	<b>N5460-250F</b>	2.0
90°	2½"	2½"	<b>N5490-250F</b>	2.0

- other threads available *contact Dixon*

## Dixon Northline Large Diameter Drafting Elbows

**Features:**

- elbows are smooth bent to degree required
- supplied hard coat anodized from maximum protection



45° elbow

Elbow Degree	Male NST Size	Female NST Swivel L/H Size	6061-T6 Aluminum Part #	Wt. Lbs.
45°	4"	4"	<b>N5445-40F40F</b>	7
45°	5"	5"	<b>N5445-50F50F</b>	9
45°	6"	6"	<b>N5445-60F60F</b>	9



60° elbow

Elbow Degree	Male NST Size	Female NST Swivel L/H Size	6061-T6 Aluminum Part #	Wt. Lbs.
60°	4"	4"	<b>N5460-40F40F</b>	7
60°	5"	5"	<b>N5460-50F50F</b>	9
60°	6"	6"	<b>N5460-60F60F</b>	9



90° elbow

Elbow Degree	Male NST Size	Female NST Swivel L/H Long Radius Size	6061-T6 Aluminum Part #	Wt. Lbs.
90°	4"	4"	<b>N5490-40F40FLR</b>	7
90°	5"	5"	<b>N5490-50F50FLR</b>	9
90°	6"	6"	<b>N5490-60F60FLR</b>	9
90°	4½"	4½"	<b>N5490-45F45FLR</b>	8

Elbow Degree	Male NST Size	Female NST Swivel L/H Short Radius Size	6061-T6 Aluminum Part #	Wt. Lbs.
90°	4"	4"	<b>N5490-40F40FSR</b>	7
90°	5"	5"	<b>N5490-50F50FSR</b>	9
90°	6"	6"	<b>N5490-60F60FSR</b>	9