

Bulkhead Fittings

female NPT fittings

Female NPT	Hole Size	Polypropylene Part #
1/2"	1-3/8"	62834
3/4"	1-3/8"	60401
1"	2-1/4"	60427
1 1/4"	2-1/4"	60403
1 1/2"	3"	60124
2"	3"	60405
3"	4-5/8"	62299 ¹

¹ 3" does not contain a washer

gaskets

Size	EPDM Part #
1/2" - 3/4"	60402
1" - 1 1/4"	60404
1 1/2" - 2"	60406
3"	60331

Application:

- for use on most poly storage tanks and many steel and fiberglass tanks

Features:

- glass reinforced polypropylene provides strength and chemical resistance
- EPDM gaskets are standard
- Viton® gaskets are available



Bolted Fittings

- Bolts are threaded into the back plate of the fitting so there are no welds or bolt holes as potential points of leakage. The fittings come standard without a gasket. However, a gasket (sold separately) is required to be installed on the inside of the tank.

Stainless Steel

Features:

- stainless steel body
- 316 stainless steel bolts
- cross-linked polyethylene gaskets are standard (sold separately)
- Viton® and EPDM gaskets are available



female NPT fittings

Size	Stainless Steel Part #
3/4"	63035
1"	62948
1 1/2"	63037
2"	63038

gaskets

Size	Cross-Linked Polyethylene Part #
3/4" - 1"	62950
1 1/2"	63042
2"	62848

Polypropylene

Features:

- polypropylene body
- 316 stainless steel bolts
- EPDM gaskets are standard (sold separately)
- Viton® gaskets are available




female NPT fittings

Size	Polypropylene Part #
3/4"	60502
1"	60505
1 1/2"	60513
2"	60516

gaskets

Size	EPDM Part #
3/4" - 1"	60498
1 1/2" - 2"	60497

Bulkhead Anchor Coupling



NPTF Pipe Thread A	UNS Straight Thread B	Hex H1	Hex H2	Length C	Std. Pkg.	Brass Part #
1/8-27"	5/8-18"	7/8"	15/16"	1.50	25	207-BH2
1/4-18"	3/4-16"	1"	1"	1.50	25	207-BH4
1/4-18"	3/4-16"	1"	1"	0.94	25	207-BH4S
3/8-18"	1-14"	1-1/8"	1-1/4"	1.31	10	207-BH6
1/2-14"	1-1/8-14"	1-1/4"	1-3/8"	1.50	10	207-BH8
3/4-14"	1-5/16-12"	1-1/2"	1-1/2"	1.50	10	207-BH12