

Tank Transport Equipment

Fusible Pipe Caps

| Size | Stainless Steel ¹ | Aluminum | Iron | Optional |
|------|------------------------------|------------|------------|----------|
| | Part # | Part # | Part # | Qty |
| 3" | 300-SFC-SS | 300-SFC-AL | 300-SFC-MI | 10 |

NOTE: Female NPSM threaded



Pipe Caps

| Size | Stainless Steel ¹ Part # | Aluminum Part # | Iron Part # | Optional Qty |
|------|--|--------------------|----------------|--------------|
| 2" | 200-PC-SS | | 200-PC-MI | |
| 3" | 300-PC-SS | 300-PC-AL | 300-PC-MI | 10 |
| 4" | 400-PC-SS | | | |

¹ PTFE gaskets are standard in stainless steel fittings.



Reducers

| Female NPSM | Male NPT | Stainless Steel ¹ Part # | Aluminum Part # | Iron Part # | Optional Qty |
|----------------|-------------|--|--------------------|----------------|-----------------|
| 3" | 2" | 3020-RD-SS | 3020-RD-AL | 3020-RD-MI | 10 |
| 4" | 3" | 4030-RD-SS ² | 4030-RD-AL | | |

PTFE gaskets are standard in stainless steel fittings.
welded fabrication



Reducing Cap

| Size | Stainless Steel ¹ Part # | Optional Qty | |
|---------|--|-----------------|--|
| 3" x 1" | 3010-RC-SS | 10 | |

NOTE: Female NPSM x Female NPT



Coupling Gaskets

| Size | Nitrile Rubber Part # | Opt Qty | PTFE Part # | Opt Qty |
|--------|--------------------------|------------|----------------|------------|
| 1-1/2" | | | 150GPCTF | |
| 2" | 200GPCBU | 25 | 200GPCTF | 10 |
| 3" | 300GPCBU | 25 | 300GPCTF | 25 |
| 4" | | | 400GPCTF | |





¹ PTFE gaskets are standard in stainless steel fittings.

¹ PTFE gaskets are standard in stainless steel fittings.