

## Sprinkler System Gauge (UL-393)

### Application

- Specifically designed for the fire sprinkler industry

### Size

- 1/4" NPT lower mount

### Features

- Bourdon tube pressure gauges with black polycarbonate case
- Snap-in clear polycarbonate window, 4" face
- White aluminum dial with stop pin, black and red markings
- Black aluminum non-adjustable pointer

### Specification

- Temperature range: -40°F to 140°F (-40°C to 60°C)

### Approvals

- ASME B40.1 Grade B (+ 3/2/3% accuracy)
- UL Listed and FM Approved for fire sprinkler service



Type	Part #
water (0-300 PSI)	SWG300-4

## Line Test Gauges

### Application

- Used for testing static or flowing pressures in hoses or nozzles

### Features

- Rocker lug swivel
- Other sizes and threads are also available; contact Dixon®

### Specifications

- Supplied with 0-300 PSI glycerine-filled 3-1/2" diameter gauge
- Freeze proof to -40°F (-40°C)

NST (NH) Thread	Hardcoated Aluminum Part #
1-1/2"	ALTG150F
2-1/2"	ALTG250F



## Three Way Gauge Valve

### Application

- Permits checking or replacing a gauge without shutting down the whole line

### Material

- Disc: rubber

NPT Thread	Working Pressure (PSI)	Brass Part #
1/4"	175	TWGV25



## PITOT Gauge

### Feature

- Supplied with handle grip, case, and fire stream/friction loss data

### Specification

- Liquid-filled gauge: 0-160 PSI is standard, other pressures available; contact Dixon®

Part #
PG8083



## Sprinkler Line Tester

### Application

- Installs on the last sprinkler head on system branch lines and controls water flow for flushing or testing the system

Inlet	Outlet	Brass Part #
1" female NPT	1" male NPSH	SLT10050

