

## Y Coupler

### Specifications

- Maximum working pressure: **100 PSI**
- Maximum temperature: **140°F (60°C)**

Required Case Qty	Nickel-Plated Brass Part #
6	GHD-500YC



## Y Valve

### Feature

- Double Y valve, swivel inlet - with Higbee cut threads (capped) to prevent cross threading

### Specifications

- Maximum temperature: **140°F (60°C)** (hot water)
- Working pressure: **100 PSI**

Description	Required Case Qty	Forged Brass Part #
double male GHT x female GHT	6	GHD-500GHY



## Plain Hose Nozzles

### Feature

- Finish: satin

### Specification

- Maximum operating pressure: **100 PSI** (water only) at **70°F (21°C)**

Size	Thread	Overall Length	Orifice	Required Case Qty	Brass Part #
3/4"	GHT	6"	1/4"	6	GHD-BN6



## GHT 4-Valve Manifold

### Feature

- Swivel inlet

### Materials

- Forged brass body, TPR handle, POM internal valve NBR seals

### Specifications

- Maximum temperature: **120°F (49°C)**
- Maximum operating pressure: **100 PSI**

Description	Required Case Qty	Part #
(4) male GH x female GHT	4	GHD-500GH4VBK



## Constant Flow Nozzle Displays

### Application

- Shatter-resistant and UV-resistant polycarbonate is able to withstand tough environmental conditions

### Features

- Seals used for true water shut off
- Easy twist spray pattern adjustment
- Sold in case quantity only (25 per case), with display

Thread	45° Spray GPM @ 100 PSI	Color	Required Case Qty	Part #
3/4" GHT	25.1	clear	1	GHD-CNB75GHT-GD
3/4" GHT	25.1	green	1	FNB75GHT-GD

