

## ABS Standard Dry Gauges Kit-Retail Package

Description	Kit Contains Part #	Required Case Qty	ABS Part #
dry gauge center back mount	GC230 (4)	1	PND-GAUGEKIT1
dry gauge lower mount	GL130 (7)		



## Polyurethane Air Hose (fittings included)

### Features

- Durable and lightweight
- Reinforced braid allows for higher working pressure
- Excellent flexibility
- Oil resistant
- Durometer: Shore A 85

### Specifications

- Temperature range: **-40°F to 155°F (-40°C to 68°C)**
- Working pressure: **210 PSI at 70°F (21°C)**

Hose ID	Length	Male NPT	Required Case Qty	Polyurethane Part #
1/4"	50'	1/4"	3	PND-450-4S



## Coil-Chief Self-Storing Air Hose (fittings included)

### Feature

- Supplied with swivel on one end

### Material

- Nylon construction

Hose ID	Length	Male NPT	Working Pressure (PSI) @ 70°F (21°C)	Required Case Qty	Nylon Part #
1/4"	12'	1/4"	<b>185</b>	3	PND-CC1412



## Polyurethane Self-Storing Air Hose (fittings included)

### Features

- Extremely flexible; resists kinking
- Impervious to abrasions and oil
- Superior elasticity and coil memory
- Both ends swivel

Hose ID	Length	Male NPT	Working Pressure (PSI) @ 70°F (21°C)	Required Case Qty	Polyurethane Part #
1/4"	25'	1/4"	<b>125</b>	3	PND-PU1425

