

Safety Vented Ball Valves

Application

- For air service only

Specification

- Pressure rating: **0-125 PSI**

Features

- Blow-out proof stem design
- Adjustable packing gland

Approval

- Vent downstream air in accordance with OSHA regulation 1910.147 for pneumatic systems

Materials

- Bronze valve
- Chromium plated ball
- RTFE seats and stuffing box ring



sliding lock mechanism

| Female NPT | Port | Required Case Qty | Bronze Part # |
|------------|----------|-------------------|---------------|
| 3/4" | standard | 3 | BBV75LV |

NOTE: Products placed in blue plastic bin with label.



Whip Hose



| Description | Required Case Qty | Part # |
|---------------------------------------------------------|-------------------|--------------|
| Whip hose 1/2" x 6', Air King x 7/8" threaded bent stem | 1 | WH50X6AKBS87 |



| Description | Required Case Qty | Part # |
|---------------------------------------------------------|-------------------|--------------|
| Whip hose 1/2" x 6', Air King x 1/2" threaded bent stem | 1 | WH50X6AKBS50 |



| Description | Required Case Qty | Part # |
|---------------------------------------------|-------------------|------------|
| Whip hose 3/4" x 6', Air King x 3500 nipple | 1 | WH75X6AK35 |

Sign Holder



| Description | Required Case Qty | Part # |
|---------------------|-------------------|------------|
| end cap sign holder | 2 | SIGNHOLDER |

End Cap Sign



| Description | Required Case Qty | Part # |
|--------------------------|-------------------|---------|
| Outside air end cap sign | 1 | OA-SIGN |

Blue Bins with Label



| Description | Required Case Qty | Contents | Part # |
|----------------------|-------------------|----------------------------------------------|-------------|
| Blue bins with label | 1 | S-12416 (2), S-13536 (13), S-12414 (5) | OA-BLU-BINS |