

TTMA Flange Spacer with 1/2" Port

| Size | Description | Aluminum Part # |
|------|---|-----------------|
| 4" | flange spacer with 1/2" female NPT port | TTFS4AL-FP50 |



TTMA Flange Extensions

Application

- Used on load arms to connect an API load coupler to a load arm

Features

- Adds a 6" space between the load arm and the tank truck
- Extension with groove provides a specified parting point to prevent excessive damage to the loading arm

| Size | Description | Aluminum Part # |
|------|---|-----------------|
| 4" | TTMA flange extension | TETF4AL |
| | TTMA flange extension with groove | TETFG4AL |
| | TTMA flange extension with 1/2" female NPT port | TETF4ALFP50 |



TETF4AL



TETFG4AL

NOTE: For flange dimensions, diagrams, and additional information, please reference canada.dixonvalve.com.

Cam & Groove Adapter x TTMA Flange

Features

- Aluminum flanges have a flat face, stainless flanges have a raised face
- Reference canada.dixonvalve.com for flange drilling standards
- Pressure rating is based on the seal of the mating part, see ratings on page 20

| Size | 356T6 Aluminum Part # | 316 Stainless Steel Part # |
|---------|-----------------------|----------------------------|
| 2" x 3" | 2030-ALT-AL | --- |
| 3" | 300-ALT-AL | 300-ALT-SS ¹ |
| 3" x 4" | 3040ALTAL | --- |
| 4" | 400-ALT-AL | 400-ALT-SS ¹ |
| 6" | 600-ALT-AL | --- |



¹ Parts are produced as a welded fabrication

Cam & Groove Coupler x TTMA Flange

Features

- Supplied standard with a nitrile rubber gasket, other gaskets available on pages 66 - 69
- Use Dixon® replacement handles only

| Size | 356T6 Aluminum Part # |
|---------|-----------------------|
| 3" | 300-DLT-AL |
| 3" x 4" | 3040DLTAL |
| 4" | 400-DLT-AL |
| 6" | 600-DLT-AL |



NOTE: For flange dimensions, diagrams, and additional information, please reference canada.dixonvalve.com.

Cam & Groove 22-1/2° Adapter x TTMA Flange

Feature

- Pressure rating is based on the seal of the mating part, see ratings on page 20

| Size | 356T6 Aluminum Part # |
|------|-----------------------|
| 4" | 40022ALTAL |



Cam & Groove 22-1/2° Coupler x TTMA Flange

Features

- Supplied standard with a nitrile rubber gasket, other gaskets available on pages 66 - 69
- Use Dixon® replacement handles only

| Size | 356T6 Aluminum Part # |
|------|-----------------------|
| 3" | 30022ALTAL |
| 4" | 40022DLTAL |



NOTE: For flange dimensions, diagrams, and additional information, please reference canada.dixonvalve.com.