

## ADS Spillguard® Probes

### Capacitance Probes

**Application**

- For materials with dielectric constant > 1.8: liquids, powders, slurries

**Features**

- 1/2" NPT sliding fitting standard; 3/4" fitting optional
- Open dome adapter and washout fitting available
- Tilt sensor optional

**Materials**

- Probe: 316 stainless
- Housing: NEMA 4X, IP66

**Specifications**

- Capacitance probe: **250°F (121°C)** maximum
- High temperature probe: **325°F (163°C)** maximum

Length	Capacitance	
	Capacitance	High-Temp
12"	A200PC12A	A200PHC12A
24"	A200PC24A	A200PHC24A
36"	A200PC36A	A200PHC36A
48"	A200PC48A	A200PHC48A
60"	A200PC60A	A200PHC60A
72"	A200PC72A	A200PHC72A
84"	A200PC84A	A200PHC84A



A200PC36A

C

### Multi-Point Ultrasonic Probes

**Application**

- For use when multiple detection points are required such as dribble mode, pump shutoff, and overflow alarm

**Features**

- Up to 5 sense points available
- Pressure sensor
- Ground verification
- Tilt storage probe only active in vertical operational position

NOTE: Built special order to customer specifications. Contact Dixon® at 877.963.4966 for more information.

