

ADS Outrage Gauges

Applications

- Set level fill point for manual/visual fill control
- Measure outage requirements on mobile tanks

Feature

- Open dome bracket

Material

- 316 stainless steel

Length	316 Stainless Steel Standard Outrage Gauge Part #	316 Stainless Steel Outrage Gauge with J Bar Part #
2'	A800G2	A800GJ2
3'	A800G3	A800GJ3
4'	A800G4	A800GJ4
5'	A800G5	A800GJ5



C

ADS Gauge Rods

Application
Used to gauge liquid levels in any mobile tank

Size
1/2" x .065 weight

Features
Laser engraved scale with 1/4" graduations
Rods come in two sections that screw together at the midpoint
Foot marks inscribed on rod at 1' intervals below the inch mark
Heavy-duty plastic handle

Material
316 stainless steel

Description	316 Stainless Steel Part #	316 Stainless Steel Part # w/sliding innage bar
gauge rod, 4' length, one piece	ADS4GR	ADS4GR-IB
gauge rod, 8' length, two piece	ADS8GR	ADS8GR-IB
gauge rod, 12' length, two piece	ADS12GR	ADS12GR-IB



laser engraving closeup

ADS Spillguard® Armored Cables

Features

- 3 or 5 pin connector
- 316 stainless steel armoured cable or yellow rubber cable
- Custom lengths available; call 877.963.4966 for more information

Armored Cables

Length	3 Pin	5 Pin
15'	A200CA3P15	A200CA5P15
20'	A200CA3P20	A200CA5P20
25'	A200CA3P25	A200CA5P25
50'	A200CA3P50	A200CA5P50



Rubber Cable¹

Length	3 Pin
25'	A200CB3P25



¹ For use with (-M) mini connectors only