lew

# Venting EZ Boss-Lock Cam & Groove

#### Application

• Transfer of fluids and solids, with a safe disconnection

Sizes

• 2", 3", and 4"

#### Features

- · In the event of an accidental disconnection under pressure, the venting feature retains the coupling and allows the stored pressure to vent off
- Povides a venting feature when used with standard cam adapters
- · The safety venting feature of this coupling doesn't require a special adapter to work as a system

#### **Materials**

- · 316 stainless steel
- 356T6 aluminum

# **Type B Coupler Coupler x Male NPT**

Size	Aluminum Part #	316 Stainless Steel Part #
2"	ALBEZ200	RLBEZ200
3"	ALBEZ300	RLBEZ300
4"	ALBEZ400	RLBEZ400

# **Type C Coupler** Coupler x Hose Shank

Size	Aluminum Part #	316 Stainless Steel Part #
2"	ALCEZ200 <sup>1</sup>	RLCEZ200 <sup>1</sup>
3"	ALCEZ300 <sup>1</sup>	RLCEZ300 <sup>1</sup>
4"	ALCEZ400 <sup>1</sup>	RLCEZ400 <sup>1</sup>


<sup>1</sup> Hose drop shank

### **Type D Coupler Coupler x Female NPT**

To	Size	Aluminum Part #	316 Stainless Steel Part #
	2"	ALDEZ200	RLDEZ200
	3"	ALDEZ300	RLDEZ300
	4"	ALDEZ400	RLDEZ400

### Туре Н Dust Cap

6		
-	TEA	
	-	







		V	-
	. []	P	
1		-	-