

# Reelcraft® 80000 Series Spring Driven Hose Reels

#### **Features**

- Reel inlet 3/4" NPTF
- Five-in-one heat treated aluminum casting incorporates main shaft, ratchet, spring arbor, and inlet/outlet plumbing in one-piece casting
- Furnished standard with PVC hose

#### **Specifications**

- Maximum temperature is 150°F (66°C) with hose
- Maximum temperature is 210°F (99°C) without hose

#### With Hose

Hose I.D.	Hose Length	Service	Working Pressure PSI	Part #
1/2"	75'	air / water	300	82075LP
1/2	100'	air / water	300	82100LP
3/4"	50'	air / water	250	83050LP


See below for bumper stops, consult Dixon® for uses other than stated services

## **Without Hose**

Hose Capacity	Service	PSI	Part #	
50' of 3/4" or 100' of 1/2"	air / water	500	83000LP	

## **Adjustable Hose Bumper Stops**

Hose I.D.	Hose O.D.		Dimensions		Reel Series	Part #	
Hose I.D.	From:	To:	B,C,E	D	Used On	Fait π	
1/4"	.438"	.625"	2-1/2"	1-1/4"	5000	1-HR1004A	
3/8"	.625"	.749"	2-1/2"	1-1/4"	5000	1-HR1004	
3/8"	.625"	.749"	3"	1-1/4"	7000	1-HR1004-3	
1/2" or 3/8" 2-wire	.750"	1.050"	3"	1-1/4"	7000	2-HR1004-3	
3/4"	1.060"	1.300"	3"	1-1/4"	7000	3-HR1004-3	
1/2"	.750"	1.050"	3-1/2"	2-7/8"	9000	2-HR1005	
3/4"	1.060"	1.380"	3-1/2"	2-7/8"	9000	3-HR1005	
1"	1.390"	1.550"	3-1/2"	2-7/8"	9000	4-HR1005	





## Reelcraft® 30000 Manual Driven Hose Reels

### **Features**

- Reel frame, spool, and drum are fabricated from heavy gauge steel
- · All bolted construction no welds
- Manual driven standard
- · Motor drive available

## Without hose

Hose I.D.	Inlet	Hose Capacity	Spool Width	Working Pressure PSI	Part #
3/4"	3/4"	100'	12"	1000	C33112L
1/2"	1/2"	200'	12"	3000	C32112M

