

Wilkerson FRLs

D18-Series Combination Units

Features

- Light weight, ready-to-mount assembly comes standard with pressure gauge and modular T-bracket/joiner assembly
- Components integrated into single unit
- Modern design and appearance
- Quick disconnect bowl / bowl guard
- 5 micron element
- 4 oz. bowl/lubricator

Regulator

- **0-125 PSI** adjusting range
- Self-relieving
- Supplied with gauge
- 1.72 oz. bowl/filter

Specifications


- Maximum operating conditions:
 - transparent bowl: 150 PSIG (10.3 bar) and **13°F to 125°F (-25°C to 52°C)**
 - metal bowl: 250 PSIG (17.2 bar) and **-13°F to 150°F (-25°C to 66°C)**

Size	Flow (SCFM)	Transparent Bowl and Guard	Metal Bowl / Sight Gauge
		Manual Drain Part #	Manual Drain Part #
1/2"	90	D18-04M	D18-04MMB

NOTE: SCFM ratings at 150 PSIG inlet pressure.



with transparent bowl and guard



D28-Series Combination Units

Features

- Light weight, ready-to-mount assembly comes standard with pressure gauge and modular T-bracket/joiner assembly
- Components integrated into single unit
- Modern design and appearance
- Quick disconnect bowl / bowl guard
- 5 micron element
- 6 oz. bowl/lubricator

Regulator

- **0-125 PSI** adjusting range
- Self-relieving
- Supplied with gauge
- 2.87 oz. bowl/filter

Specifications

- Maximum operating conditions:
 - 250 PSIG (17.2 bar) and **-13°F to 125°F (-25°C to 52°C)**

Size	Flow (SCFM)	Metal Bowl / Sight Gauge
		Manual Drain Part #
1/2"	150	D28-04MMB
3/4"	150	D28-06MMB

NOTE: SCFM ratings at 150 PSIG inlet pressure.

FRLs are designed for air service only, unless otherwise indicated.



with metal bowl

