



RRP-95-952

| Used On | Description | Part # |
|---------|--|------------|
| R16 | self-relieving repair kit | RRP-95-131 |
| R18 | relieving diaphragm assembly | RRP-96-656 |
| R26 | self-relieving repair kit | RRP-95-952 |
| R28 | relieving diaphragm assembly | RRP-96-986 |
| R30 | valve assembly: valve, spring, bottom plug O-ring | RRP-95-159 |
| R40 | valve assembly: valve, spring, retaining ring O-ring | RRP-95-161 |

Lubricator Bowls and Bowl Guards



| Used On | Description | Part # |
|---------------|--|------------|
| L08 | plastic bowl with guard and manual drain | LRP-96-736 |
| L16 | metal bowl with sight glass and manual drain | GRP-95-133 |
| | plastic bowl with guard and manual drain | GRP-95-019 |
| | plastic bowl with no drain | LRP-96-937 |
| L18 | metal bowl with sight glass, manual drain | GRP-96-636 |
| | plastic bowl with guard and manual drain | LRP-96-701 |
| L26 | metal bowl with sight glass and manual drain | GRP-95-931 |
| | plastic bowl with no drain | LRP-96-938 |
| L28 | metal bowl with sight glass, manual drain | GRP-96-644 |
| | plastic bowl with guard and manual drain | LRP-96-702 |
| L30, L40 | metal bowl with sight glass and manual drain | GRP-95-676 |
| L30, L40, L50 | plastic bowl with no drain | LRP-96-940 |

Sight Domes and Fill Plugs





| Used On | Description | Part # |
|---------------|-------------------------------------|------------|
| L08, L16, L26 | sight dome kit: dome and O-ring | LRP-95-239 |
| L08 | fill plug kit: fill plug and O-ring | LRP-96-730 |
| L16, L26, L30 | fill plug kit: fill plug and O-ring | LRP-95-253 |
| L18, L28 | sight dome assembly (new style) | LRP-96-310 |
| L30, L40, L50 | sight dome kit: dome and O-ring | LRP-95-249 |
| L40, L50 | fill plug kit: fill plug and O-ring | LRP-95-250 |

Modular Shut-Off Valves

Application

· Useful for isolating and depressurizing a downstream unit requiring maintenance or replacement



- Can be installed immediately upstream of a single unit or combination of units
- Secure to the unit with a modular sleeve or modular sleeve wall mounting bracket
- Ball-type valve operates with a 1/4 turn from open to shut position
- Can be locked in the open position
- · Left-to-right flow

| Used On | Description | Part # |
|---------------------------------|--------------------------------|------------|
| F16 F06 D16 D06 | 1/4" NPT safety shut-off valve | GPA-95-096 |
| F16, F26, R16, B26, L16. L26 | 3/8" NPT safety shut-off valve | GPA-95-097 |
| L10, L20 | 1/2" NPT safety shut-off valve | GPA-95-098 |

