

Series 1 FRLs

E73-Series Compact Combination Units

Features

- 4 oz. reservoir
- Supplied with a G230 gauge
- Connected modularly
- Includes (2) clamps and wall mounting brackets # 4314-52, (2) clamps # 4314-51, and (2) NPT pipe adapters #4315-01.

Specifications

- **5-150 PSI** range
- Inlet pressure:
 - transparent bowl: **150 PSI** and **125°F (52°C)**
 - metal bowl: **250 PSI** and **175°F (79°C)**




metal bowls

Transparent Bowl

| Port Size | Flow (SCFM) | Automatic Drain Part # | Manual Drain Part # |
|-----------|-------------|------------------------|---------------------|
| 1/4" | 70 | E73-2A | E73-2M |
| 3/8" | 70 | E73-3A | E73-3M |
| 1/2" | 70 | E73-4A | E73-4M |

Metal Bowl

| Port Size | Flow (SCFM) | Automatic Drain Part # | Manual Drain Part # |
|-----------|-------------|------------------------|---------------------|
| 3/8" | 70 | E73-3A-MB | E73-3M-MB |
| 1/2" | 70 | E73-4A-MB | E73-4M-MB |



E74-Series Standard Combination Units

Features

- 7 oz. reservoir
- Models supplied with a GC230 gauge
- Connected modularly
- Includes (2) clamps and wall mounting brackets # 4314-52, (2) clamps # 4314-51, and (2) NPT pipe adapters

Specifications

- Inlet pressure:
 - transparent bowl: **150 PSI** and **125°F (52°C)**
 - metal bowl: **250 PSI** and **175°F (79°C)**
- Pressure range: **5-150 PSI**




transparent bowl with guard

Transparent Bowl and Guard

| Port Size | Flow (SCFM) | Automatic Drain Part # | Manual Drain Part # |
|-----------|-------------|------------------------|---------------------|
| 1/2" | 150 | E74-4A | E74-4M |
| 3/4" | 140 | E74-6A | E74-6M |

Metal Bowl and Sight Glass

| Port Size | Flow (SCFM) | Automatic Drain Part # | Manual Drain Part # |
|-----------|-------------|------------------------|---------------------|
| 3/8" | 110 | E74-3A-MB | E74-3M-MB |
| 1/2" | 150 | E74-4A-MB | E74-4M-MB |
| 3/4" | 140 | E74-6A-MB | E74-6M-MB |



P8A Jumbo Combination Units

Features

- 1 qt. reservoir

Specifications


- Pressure range: **5-125 PSI**
- Inlet pressure: **250 PSI**
- Maximum temperature: **175°F (79°C)**

Metal Bowl and Sight Glass

| Port Size | Flow (SCFM) | Automatic Drain Part # | Manual Drain Part # |
|-----------|-------------|------------------------|---------------------|
| 1" | 275 | P8A-860A | P8A-860M |



with metal bowls



NOTE: SCFM ratings given at 90 PSIG inlet pressure.

FRLs are designed for air service only, unless otherwise indicated.

