356T6 aluminum



brass



316 stainless steel



Coupler x Hose Shank

Feature

 Couplers are supplied standard with a nitrile rubber gasket, other gasket types are available on pages 66 - 69

Size	356T6 Aluminum Part #	Brass Part #	316 Stainless Steel Part #
3/4" x 1/2"			RC050EZ
3/4"	AC075EZ	BC075EZ	RC075EZ
1"	AC100EZ	BC100EZ	RC100EZCR
1-1/4"		BC125EZ	RC125EZCR
1-1/2"	AC150EZ	BC150EZ	RC150EZNO
2"	AC200EZ	BC200EZ	RC200EZNO
2-1/2"	AC250EZ		
3"	AC300EZ	BC300EZ	RC300EZCR
4"	AC400EZ	BC400EZ	RC400EZCR
4"	AC400EZP1		
6"	AC600EZ		RC600EZCR
8"	AC800EZ ²		

- ¹ Includes paddle handle
- ² Dixon® and Boss-Lock cam & groove couplings do not interchange in the 8" size. Under no circumstances should the EZ Boss-Lock cam arms be used on any fitting not specifically designed for their use.



NOTE: See pages 20 - 23 for further specifications.



AC400EZP1

EZ Boss-Lock Type C Couplers with Phono Finish Shank

Application

 The shank design on these fittings was developed specifically for chemical transport hoses having Crosslinked Polyethylene (XLPE) or Ultra High Molecular Weight Polyethylene (UHMW) tubes, where shank retention can be a problem when using conventional band clamps.



- In testing tank transport hoses from a wide variety of manufacturers, the Boss-Lock PF fitting showed significant improvement in hose coupling retention over the conventional cam & groove shank design
- For best results we recommend the use of 3/4" wide band clamps found on page 469
- Other sizes available; consult Dixon® for pricing and availability

Size	316 Stainless Steel	Optional
	Part #	Qty
2"	RC200EZPF	10
3"	RC300EZPF	5

