Type B

Application

· Used primarily on irrigation and suction lines

Features

- Hot dipped, galvanized
- · Has a double pin locking lever for smooth closing action
- Type B (Bauer style) locks on the male side
- Each coupler is equipped with a safety pin to prevent accidental openings.
- These fittings are not recommended for chemicals or any hazardous type materials where the possibility of leakage would result in health or environmental concerns, consult Dixon® for recommendations



Male x Hose Shank



| Size | Galvanized Steel Part # |
|------|----------------------------|
| 2" | MC3092 |
| 3" | MC3093 |
| 4" | MC3094 |
| 6" | MC3096 |
| 8" | MC3098 |
| 10" | MC30910 ¹ |
| 12" | MC30912 ¹ |

^{1 10&}quot; and 12" supplied with ACB304 lever assist bar on page 386



Male with Male NPT

| Size | Galvanized Steel Part # |
|------|----------------------------|
| 2" | MCM3112 |
| 3" | MCM3113 |
| 4" | MCM3114 |
| 6" | MCM3116 |
| 8" | MCM3118 |



Feature

Supplied with gasket



| Size | Galvanized Steel Part # |
|------|----------------------------|
| 2" | FC3102 |
| 3" | FC3103 |
| 4" | FC3104 |
| 6" | FC3106 |
| 8" | FC3108 |
| 10" | FC31010 |
| 12" | FC31012 |

Feature

Female with Male NPT

· Supplied with gasket



| Size | Galvanized Steel Part # |
|------|----------------------------|
| 2" | FCM3122 |
| 3" | FCM3123 |
| 4" | FCM3124 |
| 6" | FCM3126 |
| 8" | FCM3128 |