

### Temperature Indicating Spray Nozzle

**Features**

- Easy-to-read dial thermometer at rear of the nozzle provides accurate and continual monitoring of water temperature
- Plastic sight window
- Gauge assembly is recessed into the rubber cover for complete protection
- Alerts the operator to shut-down the steam valve upon cold water failure, preventing scalding and steam burn injuries ensuring operator safety
- Ensures a more accurate discharge water temperature reading
- 1/2" female NPT inlet
- Black cover

**Specifications**

- Recommended for water temperatures to **200°F (93°C)**
- Maximum operating pressure: **150 PSI**
- **12.5 GPM** flow capacity



**Bronze**  
**Part #**

BWSG-TI

H

### Stainless Steel Industrial Grade Spray Nozzle

**Application**

- Recommended for use in corrosive applications where bronze and aluminum nozzles are not suitable

**Features**

- Heavy duty 300 series stainless steel body and barrel
- Variable spray pattern adjusts from a soft spray to a solid stream
- Replaceable rubber cover is specially formulated to resist a wide range of oils and chemicals and protect surrounding equipment
- 1/2" female NPT inlet

**Specifications**

- Maximum operating pressure: **150 PSI**
- Maximum flow: **12.5 GPM** at **150 PSI**
- Maximum temperature: **200°F (93°C)**



**300 Stainless Steel**  
**Part #**

300SSSG

### Brass Industrial Grade Front Lever Spray Nozzle

**Features**

- Provides effortless one hand operation; by actuating the operating lever the valve is opened/ closed and the jet power is regulated from spray to concentrated jet
- Adjusting screw on back of gun allows you to fix the desired form of jet, fixing clamp for the operating lever allows lockable position for service
- 1/2" female NPT inlet
- Durable blue rubber cover

**Specifications**

- Maximum operating pressure: **350 PSI**
- Suitable for hot water up to **122°F (50°C)**
- Flow: **6.6 GPM** at **72 PSI**



**Brass**  
**Part #**

DWG050