

## Spray Guns

### Anti-Fatigue Spray Gun



#### Features

- 3/8" female inlet
- 1/4" female outlet
- Anti-fatigue pressure compensating design

#### Specification

- Temperatures to: 320°F (160°C)

Maximum PSI	GPM	Part #
5075	12.0	HPSG
5000	10.6	HPSGW <sup>1</sup>

<sup>1</sup> W = weeping, for the car wash industry, allows a small stream of water / leak

### Pressure Spray Gun



#### Features

- 3/8" female inlet
- 1/4" female outlet

#### Specifications

- Working pressure: 4500 PSI
- Maximum temperature: 320°F (160°C)

GPM	Part #
8	HPSGL

### Heavy Duty Anti-Fatigue Spray Gun



#### Features

- 3/8" female inlet
- 1/4" female outlet
- Heavy duty anti-fatigue design
- Stainless inner tube
- Zytel® housing

#### Specifications

- Working pressure: 5800 PSI
- Maximum temperature: 320°F (160°C)

GPM	Part #
8	HPSGHD

### Pressure Spray Gun with Extension



#### Features

- 3/8" female inlet
- 22 mm x 1.5 mm female outlet
- Extension length: 19"

#### Specifications

- Working pressure: 3700 PSI
- Maximum temperature: 140°F (60°C)

GPM	Part #
8	AL9

### Pressure Spray Gun Kit with Hose, Nozzle & Lance



#### Features

- Lance: 18" with vari-spray nozzle 1.25 mm with 22 mm male inlet
- Hose: 25', 1/4" I.D. with 22 mm x 14 mm female ends
- Nozzle: 4.0 variable nozzle 0° to 80°

#### Specification

- Gun: 22 mm male inlet, 22 mm x 1.5 mm female outlet end, working pressure 2500 PSI

Part #
BIT-KIT