

Fixed Plugs

Specifications

- Working pressure: **3650 PSI**
- **7.8 GPM**
- Maximum temperature: **300°F (149°C)**

1/4" fixed quick coupling plugs

Description	Part #
1/4" female x 22 mm x 1.5 mm male	AL454 ¹
¹ For use with AL453 and AL9	

Description	Part #
1/4" male x 22 mm x 1.5 mm male	AL455F ²
² For use with AL462 only	

3/8" fixed quick coupling plugs

Description	Part #
3/8" female x 22 mm x 1.5 mm male	AL456 ¹
¹ For use with AL453 and AL9	

Description	Nickel Plated Brass Part #
3/8" female x 1/2" male plug	AL464 ²
² For use with AL462 only	

Sewer Nozzles

Specifications

- Working pressure: **3625 PSI**
- Maximum temperature: **300°F (149°C)**

Size	Orifice	303 Stainless Steel Part #
3/8"	4.5 mm	SWNZ380-045
	5 mm	SWNZ380-050

Injector Nozzles

Features

- Designed to inject cleaning solutions into high pressure discharge lines
- 3/8" male inlet and outlet

Specification

- Maximum working pressure: **4500 PSI**

Description	Orifice	Flow (GPM)	Part #
adjustable	1.8 mm	2 - 8	AL472
adjustable	2.1 mm	3 - 8	AL477
adjustable	2.3 mm	4 - 8	AL478

Line Strainer

Features

- 1/2" female inlet, 1/2" male outlet
- .60 mesh cuffed filter
- 2 additional 1/4" side ports

Specifications

- Working pressure: **100 PSI**
- **8 GPM** maximum

Aluminum Part #
AR3000-A2



AL477

