

### Unloader Valves

**Features**

- Automatically relieves pressure from the pump at shut-off
- Inlet: (2) each, 3/8" female NPT
- Outlet: 3/8" female NPT
- Bypass: (2) each, 3/8" female NPT

**Specification**

- Maximum temperature: **190°F (88°C)**

Description	Maximum Flow (GPM)	Working PSI	Part #
yellow spring	8	2,320	AL605
blue spring	8	3,650	AL606
black spring	8	4,500	AL607



**Features**

- Inlet: 3/8" female
- Outlet: 3/8" male
- Bypass: 3/8" female

**Specification**

- Maximum temperature: **190°F (88°C)**

Description	Flow (GPM)	Working PSI	Part #
VR-35 unloader valve	9	5,100	AR20831



### Thermal Relief Valve

**Features**

- Inlet: 1/2" male

**Specifications**

- Operating **PSI: 200 PSI**
- Maximum temperature: **140°F (60°C)**

**Brass**  
**Part #**

TPP140



### Safety Release Valve

**Features**

- Inlet: 3/8" male

**Specifications**

- Pressure range: **1,000 to 4,000 PSI**
- Maximum temperature: **200°F (93°C)**
- **GPM: 6**

**Part #**

AR5000-1



### Pressure Washer Braided Hose

**Specification**

- Maximum temperature: **250°F (121°C)**

I.D.	Male Swivel Inlet	Male Swivel Outlet	Pressure Rating (PSI)	Length	Rubber Part #
3/8"	3/8"	3/8"	4,000	50'	AR503830SSP



### Hand Crank Hose Reel

**Features**

- 3/8" outlet, 3/8" inlet
- Includes jumper hose, mounting bracket and crank handle
- Holds 100' of 3/8" pressure hose

**Specifications**

- Working **PSI: 3,000 PSI**
- Maximum temperature: **160°F (71°C)**

**Steel**  
**Part #**

AR-REEL100

