

GHT Zinc Fittings

Features

- Premium brass and zinc construction for maximum strength and durability
- Patented impact resistant clamp design
- Non-corroding high grade 410 stainless steel screws will not strip when tightened
- Leakproof, reusable
- For use with rubber or plastic hose
- Fits all 5/8" and 3/4" hose

Female Hose Fitting



| Part # | Optional Qty |
|--------|--------------|
| M5834F | 48           |

Male Hose Fitting



| Part # | Optional Qty |
|--------|--------------|
| M5834M | 48           |

Mender



| Part #  | Optional Qty |
|---------|--------------|
| M5834HM | 48           |

Spray Valve and Hose Assembly

Valves

Features

- Even spray valve mist provides proper moisture on paper roll ends
- Helps eliminate wrinkles and folder delivery problems, increasing pressroom production and reducing waste
- A slight flex of the hose in any direction (360°) activates the spray
- Quick action with no protruding levers, thumb depressors, triggers or other devices utilized
- Positive water seal when hose is released causes the internal valve to close and immediately shut off spray
- Sealed mechanism with no packing gland



83304



83306H

| Female NPT Size | Description     | Part # |
|-----------------|-----------------|--------|
| 1/4"            | valve only      | 83304  |
| 3/8"            |                 | 83306  |
| 1/4"            | valve with hook | 83304H |
| 3/8"            |                 | 83306H |

Hose Assembly



| Male NPT Inlet | Description | Part #  |
|----------------|-------------|---------|
| 3/8"           | 5' hose     | 8320605 |

NOTE: Additional hose lengths are available contact Dixon®