

PD-Series Diagnostic Interchange Couplings

Features

- Interchangeable with ISO15171-1, Parker PD-Series, Aeroquip FD90, Tomco Series DK
- PTFE anti-extrusion ring protects main coupler O-ring from dynamic impulse pressure damage

Specifications

- Nitrile rubber seal standard, providing a temperature range of -40°F to 250°F (-40°C to 121°C)
- Pressure rating 6000 PSI at 70°F (21°C)

Approval

• Steel componentry is plated using RoHS-compliant trivalent chrome

Female NPT Couplers

Body Size	Threads	Steel Part #
1/8"	1/8" - 27 NPT	1PDF1
1/0	1/4" - 18 NPT	1PDF2



Male NPT Couplers

Body Size	Threads	Steel
body Oizc		Part #
1/8"	1/4" - 18 NPT	1PDM2



Female NPT Plugs

Body Size	Threads	Steel Part #
1/8"	1/8" - 27 NPT	PD1F1
1/0	1/4" - 18 NPT	PD1F2



Male Threaded Plugs

Body Size	Threads	Steel Part #
	1/8" - 27 NPT	PD1M1
1/8"	1/4" - 18 NPT	PD1M2
1/0	7/16" - 20 ORB	PD10M2
	9/16" - 18 ORB	PD10M3



Dust Caps

Body Size	Pody Sizo	Nitrile
	Part #	
	1/8"	H1DC



Plug Profile

Body Size	Α	В
1/8"	0.49	0.19



