


**Dixon® Cam & Groove Type C****Coupler x Hose Shank**

356T6 aluminum



brass



316 stainless steel



unplated ductile iron

**Features**

- Finger rings are not supplied on 1" Dixon® couplings
- Couplers are supplied standard with a nitrile rubber gasket; other gasket types are available on pages 66 - 69
- Use Dixon® replacement handles only

Hose I.D.	356T6 Aluminum Part #	Brass Part #	316 Stainless Steel Part #	Unplated Ductile Iron Part #
1"	100-C-AL	100-C-BR	100-C-SS•	---
1-1/2"	150-C-AL	150-C-BR	150-C-SS	150-C-MI <sup>1</sup>
2"	200-C-AL	200-C-BR	200-C-SS	200-C-MI
3"	300-C-AL	300-C-BR	300-C-SS	300-C-MI
4"	400-C-AL	400-C-BR	400-C-SS	400-C-MI
6"	600-C-AL	600-C-BR	600-C-SS	600-C-MI

<sup>1</sup> Malleable iron

NOTE: Only use the crimp style shanks with the crimp style sleeves and ferrules. Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturers' products with Dixon® products.

**EZ Boss-Lock Cam & Groove Type C****Coupler x Hose Shank****Feature**

- Couplers are supplied standard with a nitrile rubber gasket; other gasket types are available on pages 66 - 69



Size	316 Stainless Steel Part #
1"	RC100EZCR
1-1/4"	RC125EZCR
1-1/2"	RC150EZCR
2"	RC200EZCR
3"	RC300EZCR
4"	RC400EZCR
6"	RC600EZCR

NOTE: Under no circumstances should the EZ Boss-Lock cam arms be used on any fitting not specifically designed for their use. See page 20 for further specifications.

