

### DX60-Series Hygienic Tanker Valves



**Applications**

- Used on food-grade stainless steel bulk transport trailers to safely and hygienically load and unload various products including milk, juices, chocolate, glycerin, and many types of food-grade oils

**Size**

- 3"

**Features**

- Valve housing machined from solid bar
- Hygienic single-acting wiper seal improves cleanability and durability
- Easy-lock plunger for locking valve in open position
- Patent-pending closure system to eliminate the pinch point
- Bonnet design uses standard sanitary clamp for easy removal

**Materials**

- Valve: 304 stainless steel
- Seals: FKM or nitrile rubber
- Cover: aluminum

**Specifications**

- Holding pressure: **75 PSI**
- Surface I.D. finish: <32Ra
- Connections: flange x male threaded bevel
- Temperature range: **-20°F to 212°F (-28.9°C to 100°C)**

**Approval**

- 3A-Authorization Number 1655, 53-06 (Compression-Type Valves) for CIP and COP



Size	Cover Style	Part #
3"	with aluminum cover	DX603010A1GV1
	without aluminum cover	DX603010A1GV2

NOTE: All part numbers include 3", L body style, flange to trailer x male threaded bevel, 304 stainless steel construction, standard rod, and FKM gaskets.

For other configurations, contact Dixon® at 877.963.4966



#### Valve Body Style Port Configurations

