

300# Single Jacket All Polyester Fire Hose

Materials

- Outer construction: single jacket, all polyester
- Tube construction: EPDM rubber lining

Specifications

- Proof pressure: **300 PSI**
- Service test pressure: **150 PSI** at ambient temperature **70°F (21°C)**
- Working pressure: **135 PSI** at ambient temperature **70°F (21°C)**

Approvals

- 25' and 75' lengths, UL labeled hoses and other threads and configurations are available; contact Dixon®

Uncoupled

| Size | Bowl | Length | Part # |
|--------|----------|--------|------------|
| 1-1/2" | 1-3/4" | 50' | A315-50UC |
| | | 100' | A315-100UC |
| 2" | 2-1/4" | 50' | A320-50UC |
| | | 100' | A320-100UC |
| 2-1/2" | 2-13/16" | 50' | A325-50UC |
| | | 100' | A325-100UC |
| 3" | 3-3/8" | 50' | A330-50UC |
| | | 100' | A330-100UC |



Coupled with female and male expansion ring couplings

| Size | Length | Rocker Lug Aluminum NST (NH) Part # | Rocker Lug Brass NST (NH) Part # | Rocker Lug Aluminum NPSH Part # |
|--------|--------|--|---|--|
| 1-1/2" | 50' | A315-50RAF | A315-50RBF | A315-50RAS |
| | 100' | A315100RAF | A315100RBF | A315100RAS |
| 2" | 50' | --- | --- | A320-50RAS |
| | 100' | --- | --- | A320100RAS |
| 2-1/2" | 50' | A325-50RAF | A325-50RBF | A325-50RAS |
| | 100' | A325100RAF | A325100RBF | A325100RAS |
| 3" | 50' | --- | --- | A330-50RAS |
| | 100' | --- | --- | A330100RAS |


N