

Feature

· Consult Dixon® for pricing and availability of other · Proof pressure: 500 PSI colors, lengths, threads, and configurations

Materials

Size

1-1/2"

· Outer construction: single jacket, all polyester

Coupling Type

rocker lug, aluminum, NST (NH)

rocker lug, aluminum, NST (NH)

rocker lug, aluminum, NST (NH)

rocker lug, aluminum, NPSH

rocker lug, aluminum, NPSH

rocker lug, aluminum, NPSH

Tube construction: EPDM rubber lining

Specifications

Coupled with female and male expansion ring couplings

Color

yellow

red

orange

- Service test pressure: 250 PSI •
- Working pressure: 225 PSI at ambient temperature 70°F (21°C)

Part # A515Y50RAF

A515Y50RAS

A515R50RAF

A515R50RAS

A5150R50RAF

A5150R50RAS





red

800# Double Jacket All Polyester Fire Hose

- Feature
- Consult Dixon[®] for pricing and availability of 75^t lengths and other threads and configurations
- **Specifications**

Length

50'

- Proof pressure: 800 PSI
- Service test pressure: 400 PSI •
- · Working pressure: 360 PSI at ambient temperature 70°F (21°C)

Materials

- Outer construction: double jacket, all polyester
- Tube construction: EPDM rubber lining
- **Rocker Lug** Rocker Lug **Rocker Lug** Aluminum Aluminum **Brass** Size Length NST (NH) NST (NH) NPSH **RAF Part # RBF Part # RAS Part #** 25' D815-25RAF D815-50RBF 1-1/2" 50' D815-50RAF D815-50RAS 100' D815100RAF D815100RBF D815100RAS 25' D825-25RAF 50' D825-50RBF D825-50RAS 2-1/2" D825-50RAF 100' D825100RAF D825100RBF D825100RAS

Feature

- · Other lengths, threads, couplings, and colors (yellow, red, blue, tan, orange, green, black) are available; contact Dixon®
- **Specifications**
- Proof pressure: 800 PSI at 70°F (21°C)
- Service test pressure: 400 PSI at 70°F (21°C)
- Working pressure: 360 PSI at 70°F (21°C)

Materials

- · Outer construction: double jacket, all polyester
- · Tube construction: black, synthetic rubber liner

Coupled with female and male expansion ring couplings

Size	Thread NH (NST)	Coupling Type	Length	Part #
1-1/2"	1-1/2"	rocker lug, aluminum NST (NH)	50'	D815Y50RAF
		rocker lug, aluminum NST (NH)	100'	D815Y100RAF
		rocker lug, aluminum NPSH	50'	D815Y50RAS
		rocker lug, aluminum NPSH	100'	D815Y100RAS
1-3/4"		rocker lug, aluminum NST (NH)	50'	D817Y50RAF
2-1/2"	2-1/2"	rocker lug, aluminum NST (NH)	50'	D825Y50RAF
		rocker lug, aluminum NST (NH)	100'	D825Y100RAF
3"		rocker lug, aluminum NST (NH)	50'	D8325Y50RAF



Coupled with female and male expansion ring couplings

