

## Steel Hose Cabinet



### Features

- Designed for wall installation, with or without legs, or free standing
- Supplied with holes in the back for wall mounting and 1" pipe couplings on the bottom for adding legs
- Hose, accessories, and mounting hardware not included
- Furnished without legs; if legs are required, contact Dixon®

### Material

- Red polyester coated finish on 18-gauge steel

### Approval

- Factory Mutual approved



### Steel Part #

HC30143

### Dimensions

| Width | Depth | Height |
|-------|-------|--------|
| 60"   | 15"   | 48"    |

### Basic Approved Equipment for Hose Cabinet

| Examples                |                                 |                    | Quantity Required |          |     |
|-------------------------|---------------------------------|--------------------|-------------------|----------|-----|
| Part #                  | Description                     | Page #             | Factory Mutual    | UL & FIA | ISO |
| A525-50RAF <sup>1</sup> | 2-1/2" x 50' single jacket hose | 752                | 4                 | 5        | 5   |
| A515-50RAF <sup>1</sup> | 1-1/2" x 50' single jacket hose | 752                | 2                 | 0        | 0   |
| UPP250F <sup>1</sup>    | Underwriters play pipe          | 783                | 0                 | 2        | 2   |
| BFN250NST <sup>1</sup>  | 2-1/2" adjustable fog nozzle    | 780                | 2                 | 0        | 0   |
| BFN150NST <sup>1</sup>  | 1-1/2" adjustable fog nozzle    | 780                | 1                 | 0        | 0   |
| HA2515F <sup>1</sup>    | 2-1/2" x 1-1/2" pin lug adapter | 803                | 1                 | 0        | 0   |
| 233                     | universal spanner               | 836                | 4                 | 5        | 5   |
| 189                     | adjustable hydrant wrench       | 837                | 2                 | 2        | 2   |
| PHFA6                   | 6 lb. fire axe                  | 859                | 0                 | 1        | 1   |
| FCB48                   | crowbar                         | ---                | 0                 | 1        | 1   |
| SW150 <sup>1</sup>      | 1-1/2" hose coupling gasket     | 767, 768, 782, 824 | 4                 | 5        | 5   |
| SW250 <sup>1</sup>      | 2-1/2" hose coupling gasket     | 767, 768, 782, 824 | 2                 | 0        | 0   |

<sup>1</sup> Threads must be appropriate to the authority having jurisdiction