



### Industrial Fog Nozzles

**Features**

- Delivers 30° - 60° - 90° fog pattern - shut-off - straight stream - fog
- Supplied with bumper

**Specification**

- Maximum operating pressure: **175 PSI** (water only) at **70°F (21°C)**

**Approval**

- UL listed and Factory Mutual approved for class A and B fires (except noted <sup>1,2</sup>)

Size	Thread	90° Spray GPM @ 100 PSI	Brass Part #
3/4"	GHT	---	BFN75GHT <sup>1</sup>
1"	NPSH	---	BFN75
1-1/2"		<b>32</b>	BFN100
2"		<b>85</b>	BFN150
2-1/2"		<b>108</b>	BFN200 <sup>1,2</sup>
1"	NST (NH)	<b>205</b>	BFN250
1-1/2"		<b>32</b>	BFN100NST
2-1/2"		<b>85</b>	BFN150NST
		<b>205</b>	BFN250NST <sup>2</sup>

<sup>1</sup> Not UL Listed

<sup>2</sup> Not Factory Mutual approved

NOTE: Replacement washers can be found on page 767



### Heavy Duty Industrial Fog Nozzles

**Features**

- Delivers 30° - 60° - 90° fog pattern - shut-off - straight stream - fog
- Supplied with bumper

**Approvals**

- Factory Mutual approved
- Products are to be reapproved; data subject to change in coming months

**Specification**

- Maximum operating pressure: **175 PSI** (water only) at **70°F (21°C)**

Size	Thread	90° Spray GPM @ 100 PSI	Brass Part #
1"	NPSH	---	HFN100
1-1/2"		<b>88 (+/-12)</b>	HFN150
1"	NST (NH)	---	HFN100NST
1-1/2"		<b>88 (+/-12)</b>	HFN150NST
	NYFD	---	HFN150NYFD

NOTE: Replacement washers can be found on page 767; flow rate chart on following page 781



### High Pressure Industrial Fog Nozzles

**Features**

- Combination straight stream and fog - shut-off - straight stream - fog
- Large one-piece rubber bumper with molded teeth
- Knurled base

**Specifications**

- Working pressure: **25 to 300 PSI** (water only) at **70°F (21°C)**

**Approval**

- Factory Mutual approved

Size	Thread	90° Spray GPM @ 100 PSI	Brass Part #
1-1/2"	NPSH	<b>117</b>	HPFN150
	NST (NH)		HPFN150NST

NOTE: Replacement washers can be found on page 767; flow rate chart on following page 781



### Electrical Fire All-Fog Nozzles

**Features**

- Delivers 30° - 60° - 90° fog pattern, shutoff to 30° fog, adjustable to 90° fog
- Supplied with bumper
- Use of this nozzle is not likely to prove hazardous when nozzle is held in excess of 10 feet from electrical apparatus and circuits not involving more than 250,000 volts

**Specification**

- Maximum operating pressure: **100 PSI** (water only) at **70°F (21°C)**

**Approvals**

- UL listed approved for class C fires
- Products are to be reapproved; data subject to change in coming month



Size	Thread	Wide Open GPM @ 100 PSI	Brass Part #
1-1/2"	NST (NH)	<b>96</b>	BFNE150NST
	NPSH		BFNE150

NOTE: Replacement washers can be found on page 767; flow rate chart on following page 781