

# Female x Male Adapters - Long Handle Style N56

Female Thread	Male Thread	Aluminum Extrusion - Anodized Part #
4" NPSH	2-1/2" CT *	N56-40S25_*
4" NPT	2-1/2" CT *	N56-40T25_*
	2-1/2" CT *	N56-40F25_*
4" NST (NH)	2-1/2"	N56-40F25F
4-1/2" NPSH	2-1/2" CT *	N56-45S25_*
4-1/2" NST (NH)	2-1/2" CT *	N56-45F25_*
	4"	N56-45F40F
5" NPSH	2-1/2" CT *	N56-50S25_*
5" NPT	2-1/2" CT *	N56-50T25_*
5" NST (NH)	2-1/2" CT *	N56-50F25_*
	2-1/2"	N56-50F25F
6" NPSH	2-1/2" CT *	N56-60S25_*
6" NPT	2-1/2" CT *	N56-60T25_*
6" NST (NH)	2-1/2" CT *	N56-60F25_*
	6"	N56-60F60T1



<sup>1</sup> Female NST (NH) x male NPT

## Hydrant Adapters - Rocker Lug

### Application

· Use with water

#### Specification

Maximum working pressure: 100 PSI at 70°F (21°C)

Female Thread	Male Thread	Polycarbonate Part #
1-1/2" NPSH	1-1/2" NST (NH)	POLYHA15S15F
2-1/2" NST (NH)	3/4" GHT	POLYHA2576
	1-1/2" NPSH	POLYHA2515
	1-1/2" NST (NH)	POLYHA2515F
	2" NPT	POLYHA2520T

## **Domestic Female to Male Hex Nipples**

#### Feature

• Other configurations are available, consult Dixon® for information

Female Thread	Male Thread	Cast Brass Part #
1" NPT	1-1/2" NST (NH)	FM1015F-D
1-1/2" NPT	1-1/2" NST (NH)	FM1515F-D
	2-1/2" NST (NH)	FM1525F-D
1-1/2" NST (NH)	1-1/2" NPSH	FM15F15S-D
	1-1/2" NPT	FM15F15T-D
	2-1/2" NST (NH)	FM15F25F-D
1-1/2" NPSH	1-1/2" NST (NH)	FM15S15F-D
	1-1/2" NPT	FM15S15T-D
2" NPT	1-1/2" NST (NH)	FM2015F-D
2-1/2" NPT	2-1/2" NST (NH)	FM2525F-D
2-1/2" NST (NH)	1-1/2" NST (NH)	FM25F15F-D
	1-1/2" NPT	FM25F15T-D
	2-1/2" NPT	FM25F25T-D

NOTE: All adapters are made to approved Dixon<sup>®</sup> specifications. NOTE: Replacement washers can be found on page 824

• other configurations are also available, consult Dixon® for information \_\* Customer Thread (must specify) refer to legend on pages 882-885









same size



increaser