

## Non-Rising Stem Wedge Disc Gate Valves



### Application

- For use on standpipes, fire pumps, and hydrants

### Features

- Satin finish
- Red handwheel
- Solid wedge disc with tapered seats
- Straightway pattern

### Specification

- Working pressure: **300 PSI** at 70°F (21°C)

### Approvals

- UL listed and FM approved



Inlet Female NPT	Outlet Male NST (NH)	Forged Brass Part #
2-1/2"	2-1/2"	WDGV251F
3"		WDGV3025F

## Rising Stem Wedge Disc Gate Valves

### Features

- Solid wedge disc with tapered seats
- Not recommended for wet standpipe systems, use AV250 (18-157) for this purpose, see page 860
- Other configurations are available, contact Dixon® for additional information



### Materials

- Red iron handwheel, with brass cap and chain



Inlet Female NPT	Outlet Male	Working Pressure PSI	UL Listed	Cast Brass Part #
2-1/2"	2-1/2" NST (NH)	<b>200</b>	no	RWDGV250F
3"		<b>300</b>	yes	RWDGV3025F

### Dimensions

Size	A	B closed	C	D closed	D open
2-1/2"	6-1/2"	11	2-1/2"	13-1/2"	16-1/4"
3" x 2-1/2"	6-3/16"				

