

Strainer with Spring-Loaded Check Valves

Features


- Soft seat for bubble tight shutoff, spring loaded for fast seating action
- Flow profile designed to minimize head loss

Material

- Brass with NBR seat and stainless steel strainer

Specifications

- Temperature range: 10°F to 210°F (-10°C to 100°C)
- Cracking pressure: 0.50 PSI
- Pressure rating: 1-1/2" to 2" 400 PSI WOG, 3"-4" 175 PSI WOG



Female NPT	Brass Part #
1-1/2"	BVFS20
2"	BVFS25
3"	BVFS35
4"	BVFS40

Swing Check Valves

Applications

- For use in plumbing and liquid piping systems to prevent back flow
- For horizontal or vertical use

Features

- Full flow performance with a minimum of turbulence or pressure loss
- A positive seating disc allows flow only in one direction and a screw-in cap provides easy access for periodic cleaning.

Material

- Brass disc

Specifications

- Pressure rating: 200 PSI WOG
- Temperature range: -20° to 150°F (-29°C to 66°C)



Female NPT	Brass Part #
1/2"	SWCV50
3/4"	SWCV75
1"	SWCV100
1-1/4"	SWCV125
1-1/2"	SWCV150
2"	SWCV200
3"	SWCV300
4"	SWCV400

Domestic Swing Check Valves

Features

- Class 150
- ASME B1.20.1
- 100% factory tested

Specifications

- Working pressure: 300 PSI cold, 150 PSI steam
- Temperature range: -20°F to 406°F (-29°C to 208°C)

Material

- Metal seat



Female NPT	Brass Part #
1/2"	DSCV50
3/4"	DSCV75
1"	DSCV100
1-1/4"	DSCV125
1-1/2"	DSCV150
2"	DSCV200